

Polycom[®] HDX[®] 6000 Series

Intuitive, Powerful, and Affordable Room Telepresence Solutions

Extending the reach of HD video, voice, and content sharing with powerful technology and a quick return on investment

Improve collaboration and reduce costs with affordable, easy to use room telepresence solutions from Polycom. The Polycom[®] HDX[®] 6000 series delivers high definition communication to all parts of your organization with unmatched levels of ease and simplicity.

Increase productivity and improve relationships

Now you can improve collaboration effectiveness while reducing operations and travel costs. Deliver lessons to students in classrooms around the world from a single location, align project teams in realtime across geographies, speed your time-to-market with accelerated execution across departments. With the Polycom HDX 6000 solution, you're as good as there.

Intuitive to use and manage, the HDX 6000 solution delivers telepresence experiences to standard meeting rooms, conference rooms, and other environments requiring simple connectivity. HDMI output allows for quick and seamless integration with high definition displays via a single cable, while powerful standards-based Polycom People+Content[™] technology allows users to easily and quickly share high-quality documents, spreadsheets and multimedia content. Home theater quality audio experiences are delivered by Polycom Siren[™] 22 and Polycom StereoSurround[™] sound, giving users unrivaled acoustic clarity.

Polycom offers the entire solution

The Polycom HDX 6000 series seamlessly integrates with all components of the Polycom Visual Communication portfolio, including the Polycom RealPresence[™] Experience (RPX[™]), Polycom Telepresence Experience[™] (TPX[™]), Polycom HDX telepresence solutions, Polycom RMX[®] series conference platforms, and Polycom Converged Management Application[™] (CMA[™]). Additionally, the HDX 6000 leverages our exclusive Polycom Lost Packet Recovery[™] (LPR[™]) technology for enabling high quality user experiences, even across congested public networks.

About Polycom

Polycom is the global leader in standards-based unified communications (UC) solutions for telepresence, video, and voice powered by the Polycom[®] RealPresence[®] Platform. The RealPresence Platform interoperates with the broadest range of business, mobile, and social applications and devices. More than 400,000 organizations trust Polycom solutions to collaborate and meet face-to-face from any location for more productive and effective engagement with colleagues, partners, customers, specialists, and prospects. Polycom, together with its broad partner ecosystem, provides customers with the best TCO, scalability, and security for video collaboration, whether on-premises, hosted, or cloud-delivered. Visit www.polycom.com or connect with Polycom on Twitter, Facebook, and LinkedIn.



Benefits

- Reduced operating costs and clearer communication across all parts of your organization
- Faster decision making and execution on mission critical projects
- A quality experience on any network, from a home office to a corporate board room maintained with Polycom Lost Packet Recovery[™] (LPR[™]) technology
- Incredible video quality starting from 128 Kbps

Polycom HDX 6000 Series Specifications

Package Includes

- Polycom EagleEye III or EagleEye View camera, codec, HDX Microphone Array (not with View camera model), 2 Mbps point-to-point, cables and remote control

Video Standards and Protocols

- H.264, H.264 High Profile, H.263++, H.261
- H.239 / Polycom People+Content
- H.263 & H.264 Video Error Concealment

Video Input

- 1 x Polycom EagleEye HD camera
- 1 x DVI-I

Video Output

- 1 x HDMI

People Video Resolution

- 720p, 30 fps from 512 kbps
- 720p 60/30 fps (RX/TX) from 832 kbps
- 1080p, 30/15 fps (RX/TX) from 1024 kbps
- 4SIF/4CIF, 30 fps from 128 Kbps
- 4SIF/4CIF, 60 (RX) fps from 512 Kbps
- SIF (352 x 240), CIF (352 x 288)
- QSIF (176 x 120), QCIF (176 x 144)

Content Video Resolution

- Resolutions supported: WSXGA+ (1680 x 1050), SXGA (1280 x 1024), HD (1280 x 720), XGA (1024 x 768), SVGA (800 x 600), VGA (640 x 480)
- Output: 720p (1280 x 720), 1080 (1920 x 1080), XGA (1024 x 768), SVGA (800 x 600)
- Content Sharing: People+Content™ and People+Content IP

Camera

- Polycom EagleEye III Camera
 - SMPTE 296M 1280 x 720p60 SMPTE 274M 1920 x 1080p, 60/50
 - 12x optical zoom
 - 72° FOV min
- Polycom EagleEye View camera
 - 1920 x 1080 EPTZ camera
 - 4X digital zoom
 - 55° FOV min
 - Internal stereo microphones

Audio Input

- 1 HDX microphone array supported
- 1 x 3.5 mm stereo mini (PC Audio)

Audio Output

- 1 x Aux main out (RCA)
- Digital audio on HDMI cable



Audio Standards and Protocols

- Polycom StereoSurround™ technology
- 22 kHz bandwidth with Polycom Siren™ 22 technology
- 14 kHz bandwidth with Polycom Siren 14 technology, G.722.1 Annex C
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A

Polycom Constant Clarity™ Technology

- Automatic gain control
- Automatic noise suppression
- Keyboard noise reduction
- Live music mode
- Instant adaptation echo cancellation
- Audio error concealment
- Siren Lost Packet Recovery™ (LPR™) technology

Other Supported Standards

- H.221, H.224/H.281, H.323 Annex O, H.225, H.245, H.241, H.331, H.239, H.231, H.243, H.460
- BFCP (RFC 4562)

Network

- Polycom iPriority™ for QoS
- 10/100/1000 auto NIC (RJ45)
- Auto-MDIX
- H.323 and/or SIP up to 2 Mbps
- Polycom Lost Packet Recovery™ (LPR™)
- Reconfigurable MTU size (IP only)
- API Support via Telnet
- Microsoft® Office Communications Server integration
- Microsoft® ICE support
- Microsoft® Lync™ support
- IBM® Sametime™ support

User Interface

- Directory services
- System management
 - Web-based
 - SNMP
 - Polycom Converged Management Application™ (CMA™ solution)
- CDR

- International languages (16)
- Wildcard language tool
- USB software update

Security

- Secure Web
- Security mode
- AES FIPS 197, H.235V3 and H.233/234
- FIPS 140-2 Validation Certificate (#918)
- IPv6 (DISA)
- www.polycom.com/govcerts
- Secure password authentication

Options

- Polycom Touch Control
- Polycom EagleEye Director
- 1080p
- IP 7000 speakerphone integration
- HDX Media Center options
- RTV/CCCP

Electrical

- Auto sensing power supply
- Typical operating voltage/power
 - 189VA @ 115V @ 60 Hz @ .67 PF
 - 192VA @ 230V @ 60 Hz @ .66 PF
 - 196VA @ 230V @ 50 Hz @ .65 PF

Environmental Specification

- Operating temperature: 0—40°C
- Operating humidity: 10—80%
- Non-operating temperature: -40°—70°C
- Non-operating humidity (non-condensing): 10—90%
- Maximum altitude: 10,000 feet

Physical Characteristics

- HDX 6000 base box with removable stand
 - 13.9" x 5.1" x 11" (H/W/D standing)
 - 12 lbs (5.5 kg)

Warranty

- One-year return to factory parts and labor

Polycom Worldwide Headquarters
4750 Willow Road, Pleasanton, CA 94588
1.800.POLYCOM or +1.925.924.6000
www.polycom.com

