

Intelligent Solutions for Today's Complex World

providing a path towards increased RMR



Video Surveillance & Access Control

Using cutting edge technology to **DETECT**, **RECOGNIZE**, and **ALERT**!



FACIAL RECOGNITION



LINE CROSSING COUNTING



HUMAN DETECTION



LICENSE PLATE RECOGNITION



VEHICLE DETECTION

FACIAL RECOGNITION: With Facial Recognition an alarm can be triggered if a face is detected in a designated area. Alarms can also be triggered on specific faces, or recognized vs. unrecognized faces. Facial Recognition **Captures**, **Recognizes**, and **Stores** faces and you can search by face during playback. Sends real time alerts when there is a friendly or unfriendly face in view. It's a self-contained system (camera & recorder) with no licenses or monthly fees.

LINE CROSSING COUNTING: Line Crossing has the ability to maintain counts of people and/or vehicles. Alarms can also be triggered on excessive counts to control crowd density, which is an important feature. Line Crossing alerts you when someone enters an area they are not supposed to be in.

HUMAN DETECTION: Virtually eliminates false motion alarms! Speco's analytic cameras and recorders with human detection can notify you of people in the scene and ignore everything else such as animals and precipitation. Alarms can be triggered if people enter view or a pre-defined region. Alarms can also be tailored to trigger upon entrance or exit of region.

LICENSE PLATE RECOGNITION: Taking Vehicle Detection to the next level with the addition of Licesne Plate Recognition. **Capture** and **Search** by license plate or by date and time.

VEHICLE DETECTION: Trigger motion that matters! Speco's analytic cameras and recorders with Vehicle Detection will detect vehicles, motorcycles, and even bicycles. Alarms can be triggered if vehicles enter entire view or a pre-defined region. Alarm can also be tailored to trigger upon entrance or upon exit of a region.

Speco's Intelligent Solutions provide you with answers for today's problems.

Table of Contents IP Cameras | pages 4-28 HD-TVI Cameras | pages 29-47 SecureGuard® | page 48 Recorders & ZIPKITS | pages 49-59 Access Control | pages 60-66

O8FD4M

3.6-11 mm motorized lens, dark gray housing

8MP (4K) H.265 Flexible Intensifier® Technology Dome IP Camera with Junction Box

- Flexible Intensifier® Technology to fit any lighting application
- Intensifier[®] mode allows for a vivid color image without IR LEDs in low light
- Supports up to ultra HD 4K resolution
- Motorized lens with auto focus for easy installation
- Adaptive high power IR LEDs for a vivid image with no saturation in darkness
- IR range: 130' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True WDR (wide dynamic range) operation
- Supports H.265, H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- Sensor input and relay output
- Glacier Series: Operates -40°F

• Built-in heater and anti-fog glass reduces condensation under any weather condition

- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- White Chameleon Cover[™] included: snaps on and can be painted to match any décor!

POEINJ

12.95W

PoE Injector

- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



2-WAY AUDIO

AY NIGHT

Included White Chameleon Cover™

Optional Accessories

IP 4K INT IR H.265 WDR FORMS POE 1P67

PSW5 12VDC

Power Supply

IP 4K INT IR H.265 TRUE POE POE





2-WAY Audio

O8FB7M

3.6-11 mm motorized lens, dark gray housing

8MP (4K) H.265 Flexible Intensifier® Technology Bullet IP Camera with Junction Box

- Flexible Intensifier® Technology to fit any lighting application
- Intensifier[®] mode allows for a vivid color image without IR LEDs in low light
- Supports up to ultra HD 4K resolution
- Motorized lens with auto focus for easy installation
- Adaptive high power IR LEDs for a vivid image with no saturation in darkness
- IR range: 130' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True WDR (wide dynamic range) operation
- Supports H.265, H.264 and MJPEG codecs
- 2-way audio communication
- Built-in heater and anti-fog glass reduces condensation under any weather condition

- Micro SD card slot (card not included)
- Sensor input and relay output
- IP67 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines











POEINJ 12.95W PoE Injector PSW5 12VDC Power Supply

O8D8M

2.8-12mm motorized lens, white housing

8MP (4K) Dome IP Camera with Advanced Analytics and Junction Box

- Captures up to 8MP @ 30fps
- Up to 4x optical zoom
- H.265/H.264/MJPEG compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 98' to 164' (depending on scene reflection)
- True WDR (wide dynamic range) operation
- Micro SD card slot up to 256GB (card not included)
- · Line crossing, object detection region intrusion, and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection*
- Glacier Series: Operates -40°F
- Built-in microphone
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Built-in analytics with NR and HR Series Recorders

O8B8M

2.8-12mm motorized lens, white housing

8MP (4K) H.265 Bullet IP Camera with Advanced Analytics and Junction Box

- Captures up to 8MP @ 30fps
- Up to 4x optical zoom
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 229' (depending on scene reflection)
- True WDR (wide dynamic range) operation
- Micro SD card slot up to 256GB (card not included)
- Line crossing, object detection, region intrusion, and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection*
- Glacier Series: Operates -40°F
- Two-way audio support
- IP67 compliant, weather resistant
- Built-in analytics with NR and HR Series Recorders

- Junction box included for convenience
- 2-way audio communication
- 5 year warranty
- NDAA Compliant*

POEINJ

12.95W

PoE Injector

- *with compatible Speco Blue recorder
- **Products are in compliance with NDAA Section 889 Part B Guidelines

PSW5 12VDC

Power Supply





Optional Accessories



speco technologies

ZOOM AUDIO





OPERATES

IN -40°F

M



- Junction box included for convenience
- 5 year warranty
- NDAA Compliant**
- *with compatible Speco Blue recorder
- **Products are in compliance with NDAA Section 889 Part B Guidelines

POEINJ

PoE Injector

Optional Accessories



Power Supply





COMPLIANT



OPERATES

IN -40°F

M

CLT3

Ceiling Mount

O8T8M

2.8-12mm motorized lens, white housing

8MP (4K) H.265 Turret IP Camera with Advanced Analytics and Junction Box

- Captures up to 8MP @ 30fps
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 164' (depending on scene reflection)
- True WDR (wide dynamic range) operation
- Micro SD card slot up to 256GB (card not included)
- Line crossing, object detection, region intrusion,
- and video blurring detection*
- Face Detection and capture*
- Human/Vehicle detection and counting*
- Glacier Series: Operates -40°F
- Built-in microphone
- IP67 compliant, weather resistant
- Built-in analytics with NR and HR Series Recorders

O8VD1

2.8mm fixed lens, white housing

8MP (4K) H.265 Dome IP Camera with Analytics and Junction Box

- Captures up to 8MP resolution @ 20fps
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 100' (depending on scene reflection)
- Digital WDR (wide dynamic range)
- Micro SD card slot up to 128GB (card not included)
- Conformant with ONVIF Profile T
- Line crossing, object detection, region intrusion and video blurring detection*
- Built-in microphone

6

- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

- Junction box included for convenience • Conformant with ONVIF Profile T
 - 5 year warranty

POEINJ

12.95W

PoE Injector

*with compatible Speco Blue recorder **Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories












ZOOM FOCUS NIGHT





- 5 year warranty
- NDAA Compliant*

12.95W

PoE Injector

*with compatible Speco Blue recorder

**Products are in compliance with NDAA Section 889 Part B Guidelines



Optional Accessories



12VDC

Power Supply



Flush

Mount





O8VB1 2.8mm fixed lens, white housing

8MP (4K) H.265 Bullet IP Camera with Analytics and Junction Box

- Captures up to 8MP resolution @ 20fps
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 100' (depending on scene reflection)
- Digital WDR (wide dynamic range)
- Micro SD card slot up to 128GB (card not included)
- Conformant with ONVIF Profile T
- Line crossing, object detection region intrusion and video blurring detection*
- IP67 compliant, weather resistant
- Junction box included for convenience
- Glacier Series: Operates -40°F
- Built-in analytics with NR and HR Series Recorders

O8VT1

2.8mm fixed lens, white housing

8MP (4K) H.265 Turret IP Camera with Analytics and Junction Box

- Captures up to 8MP resolution @ 20fps
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 100' (depending on scene reflection)
- Digital WDR (wide dynamic range)
- Micro SD card slot up to 128GB (card not included)
- Conformant with ONVIF Profile T
- · Line crossing, object detection region intrusion and video blurring detection*
- Built-in microphone
- IP67 compliant, weather resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

- 5 year warranty
- NDAA Compliant**

*with compatible Speco Blue recorder

**Products are in compliance with NDAA Section 889 Part B Guidelines

• Glacier Series: Operates -40°F

*with compatible Speco Blue recorder **Products are in compliance with NDAA

Section 889 Part B Guidelines

5 year warranty

NDAA Compliant*

PSW5 PoE Injector

POEIN

12.95W

12VDC Power Supply

Optional Accessories

Corner Mount

CMT1 Pole Mount

OMPLIANT

PMT1

CIT1 Ceiling Moun

OPERATES

IN -40°







Optional Accessories













O6MDP3

1.07mm fisheye lens, white housing

6MP Indoor 360° Panomorph **IP** Camera with Junction Box

- Captures up a 360° view @ 30fps
- Provides a 360° view from ceiling or 180° view from wall
- H.265/H.264/MJPEG compression supported
- De-warp views from the camera or recorder*
- Built-in standard PoE (IEEE 802.3af)
- Triple codec (H.265/H.264/MJPEG)
- Smart IR with range up to 100' (depending on scene reflection)
- Micro SD card slot up to 128GB (card not included)
- Junction box included for convenience
- Conformant with ONVIF Profile T
- 5 year warranty

*with compatible Speco NRE recorder





CLT5

Ceiling Moun

Optional Accessories



O6FD4M

2.7-12mm motorized lens, dark gray housing

6MP H.265 Flexible Intensifier[®] Technology Dome IP Camera with Junction Box

- Flexible Intensifier® Technology to fit any lighting application
- Supports up to 6MP
- · Motorized lens with auto focus for easy installation
- Adaptive high power IR LEDs for a vivid image with no saturation in darkness
- IR range: 130' (depending on scene reflection)
- Image presets for different scenarios
- Built-in standard PoE (IEEE 802.3af)
- True WDR (wide dynamic range) operation
- Supports H.265, H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- Sensor input and relay output
- Glacier Series: Operates -40°F
- Built-in heater and anti-fog glass reduces
- condensation under any weather condition

- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience

6 MP

- Conformant with ONVIF Profile S
- 5 year warranty
- White Chameleon Cover[™] included: snaps on and can be painted to match any décor!

- TAA Compliant
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines





COMPLIANT

Optional Accessories



OPERATES

IN -40°

M



12VDC Power Supply

Flush Mount





IP 6 IR H.265 *> U H.264 DAV NIGHT POE

IR H.265 TRUE POE SLOT IP67

ZOOM 2-WAY FOCUS AUDIO





O6FB7M 2.7-12mm motorized lens, dark gray housing

6MP H.265 Flexible Intensifier® Technology **Bullet IP Camera with Junction Box**

- Flexible Intensifier[®] Technology to fit any lighting application
- Supports up to 6MP
- Motorized lens with auto focus for easy installation
- Adaptive high power IR LEDs for a vivid image with no saturation in darkness
- IR range: 130' (depending on scene reflection)
- Image presets for different scenarios
- Built-in standard PoE (IEEE 802.3af)
- True WDR (wide dynamic range) operation
- Supports H.265, H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- Built-in heater and anti-fog glass reduces condensation under any weather condition

O5D2

2.8mm fixed lens, white housing

5MP Dome IP Camera with Advanced Analytics and Junction Box

- Supports up to 5MP @ 30fps
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 256GB (card not included)
- Line crossing, object detection region intrusion and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection**
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Built-in analytics with NR and HR Series Recorders
- Junction box included for convenience

- Sensor input and relay output
- IP67 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- 5 year warranty
- TAA Compliant
- NDAA Compliant*
- * Products are in compliance with NDAA Section 889 Part B Guidelines









IP 6 INT IR H.265 WDR POE SLOT AUDIO

- Cloud recording and playback support*
- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant***
- *with Speco Cloud subscription service
- * * with compatible Speco Blue recorder
- * * * Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories



O5VLWM Wall Mount

M



* * * Products are in compliance with

POEIN

12.95W

PoE Injecto

NDAA Section 889 Part B Guidelines

OPERATES

IN -40°

CIT1 Ceiling

Moun

M

O4VLWM

Wall Moun

CMT1

Corner Moun

COMPLIANT

Optional Accessories

PMT1

Pole Mount

PSW5

12VDC

Power Supply

- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 256GB (card not included)
- Line crossing, object detection region intrusion and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection**
- IP67 compliant, weather resistant

- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

05P2 2.8mm fixed lens, white housing

5MP H.265 Mini-Dome IP Camera with Advanced Analytics and Wall Mount

- Supports up to 5MP @ 30fps
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 65' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 256GB (card not included)
- Line crossing, object detection region intrusion and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection**
- IP67 compliant, weather resistant
- Wall mount included
- Built-in analytics with NR and HR Series Recorders

O5D2M

2.8-12mm motorized lens, white housing

5MP Dome IP Camera with Advanced Analytics and Junction Box

- Supports up to 5MP @ 30fps
- Up to 4x optical zoom
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 165' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 256GB (card not included)
- Line crossing, object detection region intrusion and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection**
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Built-in analytics with NR and HR Series Recorders
- Two Way Audio Ready

- Cloud recording and playback support'
- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant***

*with Speco Cloud subscription service

- **with compatible Speco Blue recorder
- ***Products are in compliance with NDAA Section 889 Part B Guidelines



IP 5 IR H.265 TRUE *) DAY DAY NIGHT SLOT POE IP67







- Cloud recording and playback support*
- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant* * *
- *with Speco Cloud subscription service
- **with compatible Speco Blue recorder
- ***Products are in compliance with NDAA Section 889 Part B Guidelines



M

Optional Accessories

OMPLIANT



5

2.8-12mm motorized lens, white housing

5MP Bullet IP Camera with Advanced Analytics and Junction Box

- Supports up to 5MP @ 30fps
- Up to 4x optical zoom
- Adaptive IR LEDs reduce IR saturation

O5B2M

- IR range: Up to 230' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 256GB (card not included)
- Line crossing, region intrusion, and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection**
- Built-in analytics with NR and HR Series Recorders
- Junction box included for convenience
- Cloud recording and playback support*
- Two Way Audio Ready

O5T2M

2.8-12mm motorized lens, white housing

5MP Turret IP Camera with Advanced Analytics and Junction Box

- Supports up to 5MP @ 30fps
- Up to 4x optical zoom
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 165' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 256GB (card not included)
- · Line crossing, object detection region intrusion and video blurring detection*
- Face/Human/Vehicle/Scene Change Detection**
- Built-in analytics with NR and HR Series Recorders
- Junction box included for convenience
- Cloud recording and playback support*

- IP67 compliant, weather resistant
- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant**
- * with Speco Cloud subscription service
- **with compatible Speco Blue recorder
- * * * Products are in compliance with NDAA Section 889 Part B Guidelines



Optional Accessories

SERIES ZOOM

R H.265 TRUE WDR ANALYTICS POE SLOT SLOT IP67





• IP67 compliant, weather resistant

- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant**

POEINJ

12.9.5W

PoE Injector

- * with Speco Cloud subscription service **with compatible Speco Blue recorder
- * * * Products are in compliance with
- NDAA Section 889 Part B Guidelines



IN -40°F

M



CMT1

Optional Accessories



- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: 98' (depending on scene reflection)
- Micro SD card slot up to 128GB (card not included)
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Line crossing, object detection region intrusion and video blurring detection*
- Face Detection and capture*
- Human/Vehicle detection and counting?
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant

O4B6

2.8mm fixed lens, white housing

4MP H.265 Bullet IP Camera with Advanced Analytics and Junction Box

- Supports up to 4MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: 98' (depending on scene reflection)
- Micro SD card slot up to 128GB (card not included)
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- IP67 compliant, weather resistant
- Line crossing, object detection region intrusion and video blurring detection*
- Face Detection and capture*
- Human/Vehicle detection and counting*
- Built-in analytics with NR and HR Series Recorders

- Junction box included for convenience
 - Conformant with ONVIF Profile T
- 5 year warranty

POEINJ

12.95W

PoE Injector

*with compatible Speco Blue recorder

PSW5

12VDC

Power Supply



Optional Accessories

FMT1 Flush

Moun

PMT1 Pole Mount

O5VLWM Dome Wall C Mount

CMT1 Corner Mount



Junction box included for convenience
Conformant with ONVIF Profile T

.....

12.95W PoE Injector

• 5 year warranty

*with compatible Speco Blue recorder



Optional Accessories

PMT1

Pole Mount





12VDC

Power Supply





CLT1

Ceiling Mount



4MP H.265 Mini-Dome IP Camera with Advanced Analytics and Wall Mount

- Supports up to 4MP @ 30fps
- Adaptive IR LEDs reduce IR saturation
- IR range: 65' max (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- IP67 compliant, weather resistant
- Line crossing, object detection region intrusion and video blurring detection*
- Face Detection and capture*
- Human/Vehicle detection and counting*
- Built-in analytics with NR and HR Series Recorders

- Junction box included for convenience
- Conformant with ONVIF Profile T
- 5 year warranty

*with compatible Speco Blue recorder



Optional Accessories



PoE Injector

inese toohnol

c(IL)u

2.8-12mm motorized lens, white housing

4MP H.265 Dome IP Camera with Advanced Analytics and Junction Box

- Supports up to 4MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported

O4D7M

- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- Motorized lens with auto focus for easy installation
- IR range: Up to 165' (depending on scene reflection)
- Micro SD card slot up to 128GB (card not included)
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Line crossing, object detection region intrusion and video blurring detection *
- Face Detection and capture*
- Human/Vehicle detection and counting*
- Built-in analytics with NR and HR Series Recorders

O4B7M

2.8-12mm motorized lens, white housing

4MP H.265 Bullet IP Camera with Advanced Analytics and Junction Box

- Supports up to 4MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- Motorized lens with auto focus for easy installation
- IR range: Up to 230' (depending on scene reflection)
- Micro SD card slot up to 128GB (card not included)
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Line crossing, object detection region intrusion and video blurring detection*
- Face Detection and capture*
- Human/Vehicle detection and counting*
- Built-in analytics with NR and HR Series Recorders

- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience
- Conformant with ONVIF Profile T
- 2-way audio communication
- 5 year warranty

* with compatible Speco Blue recorder



ZOOM FOCUS

IR H.265 TRUE WDR ANALYTICS POE BAY SLOT IP67 IK10





• Junction box included for convenience

POEINJ

12.95W

PoE Injecto

- IP67 compliant, weather resistant
- 2-way audio communication
- Conformant with ONVIF Profile T
- 5 year warranty

*with compatible Speco Blue recorder

Optional Accessories

CLT3 Ceiling

Moun

OPERATES

IN -40°F

PMT1

Pole Mount

PSW5

12VDC

Power Supply

CMT1

Corner Mour

04T7M

2.8-12mm motorized lens, white housing

4MP H.265 Turret IP Camera with Advanced Analytics and Junction Box

- Supports up to 4MP @ 30fps
- Adaptive IR LEDs reduce IR saturation
- Motorized lens with auto focus for easy installation
- IR range: Up to 165' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- Line crossing, object detection region intrusion and video blurring detection*
- Face Detection and capture*
- Human/Vehicle detection and counting*
- Micro SD card slot up to 128GB (card not included)
- IP67 compliant, weather resistant



2.8mm fixed lens, white housing

4MP Dome IP Camera with Analytics and Junction Box

- Supports up to 4MP @ 30fps
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Micro SD card slot up to 128GB (card not included)
- Line crossing, object detection region intrusion and video blurring detection*
- Glacier Series: Operates -40°F
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience
- Conformant with ONVIF Profile T
- Built-in analytics with NR and HR Series Recorders

- Built-in analytics with NR and HR Series Recorders
- Junction box included for convenience
- Conformant with ONVIF Profile T
- 5 year warranty

*with compatible Speco Blue recorder





IP 4 IR H.265 TRUE * DAY NIGHT MATTICS SLOT POE FOCUS IP67





NDAA Compliant**

*with compatible Speco Blue recorder

- **Products are in compliance with NDAA Section 889 Part B Guidelines
- NDAA COMPLIANT



Optional Accessories



POEINJ

12.95W

PoE Injecto



Mount

Power Supply







CMT1 Corner Moun

O4VB1 2.8mm fixed lens, white housing

4MP H.265 Bullet IP Camera with Analytics and Junction Box

- Supports up to 4MP @ 30fps
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- Line crossing, object detection, region intrusion, and video blurring detection*
- IP67 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile T
- Built-in analytics with NR and HR Series Recorders



- NDAA Compliant**
- *with compatible Speco Blue recorder
- * * Products are in compliance with NDAA Section 889 Part B Guidelines





OMPLIANT

H.265 (AV) ANALYTICS SLOT POE IP67



OPERATES IN -40°F

M

O4VT1

2.8mm fixed lens, white housing

4MP H.265 Turret IP Camera with Analytics and Junction Box

- Supports up to 4MP @ 30fps
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- · Line crossing, object detection, region intrusion, and video blurring detection*
- IP67 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile T
- Built-in analytics with NR and HR Series Recorders

5 year warranty

NDAA Compliant*

*with compatible Speco Blue recorder

** Products are in compliance with NDAA Section 889 Part B Guidelines









CMT1 Corner Mount

IN -40°F

M

O4VB1M H.265 AV ANALYTICS SLOT FOCUS POE IP67 2.8-12mm motorized lens, white housing 4MP H.265 Bullet IP Camera with Analytics and Junction Box • Supports up to 4MP @ 30fps 5 year warranty • IR range: Up to 167' (depending on scene reflection) NDAA Compliant** Built-in standard PoE (IEEE 802.3af) • True Day/Night operation (IR cut filter) *with compatible Speco Blue recorder • H.265/H.264 compression supported * * Products are in compliance with NDAA Section 889 Part B Guidelines • Digital WDR (wide dynamic range) Motorized lens with auto focus for easy installation OPERATES IN -40°F • Glacier Series: Operates -40°F Micro SD card slot up to 128GB (card not included)

- Line crossing, object detection, region intrusion, and video blurring detection*
- IP67 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile T
- Built-in analytics with NR and HR Series Recorders



2.8-12mm motorized lens, white housing

4MP H.265 Turret IP Camera with Analytics and Junction Box

- Supports up to 4MP @ 30fps
- IR range: Up to 167' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Motorized lens with auto focus for easy installation
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- 1ch Built-in Microphone
- Line crossing, object detection, region intrusion, and video blurring detection*
- IP67 compliant, weather resistant
- Built-in analytics with NR and HR Series Recorders

POEINJ 12.95W PoE Injector

EF

Junction box included for convenience

Conformant with ONVIF Profile T

*with compatible Speco Blue recorder * * Products are in compliance with

NDAA Section 889 Part B Guideline

5 year warranty

NDAA Compliant**

PMT1 PSW5 12VDC Power Supply

CMT1 Corner Mount

R H.265 DAY NIGHT ANALYTICS SLOT POE FOCUS **4** MP IP67





M

Optional Accessories



Optional Accessories



CLT1

O4P25X IP 4 IR H.265 H.264 SUPPORT SCALE NO DAY AMALTICS WDR SLOT POE+ IP66 4.8-120mm 25x optical zoom lens, white housing

4MP 25X PTZ IP Camera with Advanced Analytics, Smart Tracking and Wall Mount Bracket

- Supports up to 4MP @ 30fps
- 25x optical zoom
- Power with built in PoE+ support (IEEE 802.3bt) or included 24VDC power adapter
- True Day/Night operation (IR cut filter)
- True WDR (wide dynamic range operation)
- IR range: Up to 328' (depending on scene reflection)
- Micro SD card slot up to 256GB (card not included)
- Face Detection and capture*
- Human/Vehicle detection with Smart Tracking*
- Line crossing, object detection, region intrusion, and video blurring detection*
- Built-in analytics with NR and HR Series Recorders
- IP66 compliant, weather resistant

- Two-way audio support
- Wall mount included
- Conformant with ONVIF Profile T
- 1 year warranty
- NDAA Compliant**

*with compatible Speco Blue recorder

- ** Products are in compliance with
 - NDAA Section 889 Part B Guidelines









2-WAY AUDIO

AUDIO

O4P30X2 IP & IR H.265 H.264 SUPPORT SLOT POE+ IP66

4.7-141 mm 30x optical zoom lens, white housing

4MP 30X IP PTZ Camera with Advanced Analytics, Smart Tracking and Wall Mount Bracket

- Supports up to 4MP @ 30fps
- Up to 30x optical zoom and 16x digital zoom
- Power with built in PoE+ support (IEEE 802.3at) or included 24VDC power adapter
- True Day/Night operation (IR cut filter)
- True WDR (wide dynamic range operation)
- IR range: Up to 328' (depending on scene reflection)
- Micro SD card slot up to 256GB (card not included)
- Face Detection and capture*
- Human/Vehicle detection with Smart Tracking*
- Line crossing, object detection, region intrusion, and video blurring detection*
- Built-in analytics with NR and HR Series Recorders
- Two-way audio support
- IP66 compliant, weather resistant

- Wall mount included
- Conformant with ONVIF Profile T
- 1 year warranty

*with compatible Speco Blue recorder







Indoor/Outdoor | 2MP PTZ/FR IP Cameras



- IP66, compliant, weather resistant
- Wall mount bracket included





7-22mm motorized lens, white housing

2MP H.265 Facial Recognition **Bullet IP Camera with Junction Box**

- Supports up to 2MP @ 30fps
- Built-in Face Detection and Recognition*
- Face Recognition Search with compatible Speco Recorder
- Built-in white LED for optimum face capture
- Built-in Analytics for object detection and line crossing
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- Built-in Micro SD slot up to 128GB (card not included)
- 2-way audio communication
- IP67 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- 5 year warranty
- *Must use with NRE NVR for Facial Recognition



Optional Accessories



PSW5

12VDC Power Supply



PMT1

Pole Mount





POFINI 12.95W PoE Injector

EF

O2iD8 3.6mm fixed lens, white housing

2MP Ultra Intensifier[®] Dome IP Camera with Junction Box

- Next generation of Intensifier[®] technology provides an even more vivid color image in low light situations
- Preset image modes offer convenient settings for different environments
- Supports up to Full HD at 1080p resolution @ 30fps
- H.265/H.264/MJPEG compression supported
- Built-in standard PoE (IEEE 802.3af)
- Glacier Series: Operates -40°F
- True WDR (wide dynamic range) operation
- Micro SD card slot for edge recording (card not included)
- IP66 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience

- Conformant with ONVIF Profile S
- Black Chameleon Cover[™] included: snaps on and can be painted to match any décor!

NDA

COMPLIANT

- 5 year warranty
- TAA Compliant
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines



speco technologies

IP 2 1265 127 TRUE VE SLOT IP66 IK10



OPERATES

IN -40°I

M

WMiD8 Wall Mount

Optional Accessories

PSW5

12VDC

Included Black

O2iB68

3.6mm fixed lens, dark gray housing

2MP Ultra Intensifier[®] Bullet IP Camera with Junction Box

- Next generation of Intensifier[®] technology provides an even more vivid color image in low light situations
- Preset image modes offer convenient settings for different environments
- Supports up to Full HD at 1080p resolution @ 30fps
- H.265/H.264/MJPEG compression supported
- Built-in standard PoE (IEEE 802.3af)
- Glacier Series: Operates -40°F
- · Built-in temperature and humidity sensor control automatic heater operation
- True WDR (wide dynamic range) operation
- IP68 compliant, weather resistant
- Junction box included for convenience

- Conformant with ONVIF Profile S
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines







12.95W PoE Injector

O2VB1 2.8mm fixed lens, white housing

2MP H 265 Bullet IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- 3.5mm mic input
- Line crossing, object detection, region intrusion, and video blurring detection*
- IP67 compliant, weather resistant
- Built-in analytics with NR and HR Series Recorders
- Junction box included for convenience



2.8mm fixed lens, white housing

2MP H.265 Turret IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- Line crossing, object detection, region intrusion, and video blurring detection*
- Built-in mic
- IP67 compliant, weather resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

- Conformant with ONVIF Profile T
- 5 year warranty
- *with compatible Speco Blue recorder

POEINJ PSW5 12VDC 12.95W PoE Iniecto Power Supply

PMT1 Pole Moun

Optional Accessories

H.265 (DAY NIGHT ANALYTICS SLOT POE IP67

CLT1 Ceilino Moun CMT1 Corner Moun

OPERATE IN -40°







Optional Accessories



• Conformant with ONVIF Profile T

*with compatible Speco Blue recorder

5 year warranty



PSW5 12VDC Pole Moun Power Supply





CMT1 Corner Moun
















O2VB1V

2.8-12mm varifocal lens, white housing

2MP H 265 Bullet IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 164' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- 3.5mm audio input
- Line crossing, object detection, region intrusion, and video blurring detection*
- IP67 compliant, weather resistant
- Built-in analytics with NR and HR Series Recorders
- Junction box included for convenience



5 year warranty

*with compatible Speco Blue recorder



12VDC Power Supply

PMT1 Pole Moun

IR H.265 (*) DAY MIGHT SLOT POE IP67

Optional Accessories

CLT1 Ceiling CMT1

OPERATE

IN -40°F

Corner Moun



2.8-12mm varifocal lens, white housing

2MP H.265 Turret IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 164' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- Line crossing, object detection, region intrusion, and video blurring detection*
- Built-in mic
- IP67 compliant, weather resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

- Conformant with ONVIF Profile T
- 5 year warranty

*with compatible Speco Blue recorder



POFINI 12.9.5W PoE Injector

PSW5 12VDC Power Supply





OPERATES

CMT1 Corner Moun



O2VT1VN

2.8-12mm varifocal lens, white housing

2MP Turret IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 164' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- Line crossing, object detection, region intrusion, and video blurring detection*
- Built-in mic
- IP67 compliant, weather resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders



2MP Turret IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- Line crossing, object detection, region intrusion, and video blurring detection*
- Built-in mic
- IP67 compliant, weather resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant**

*with compatible Speco Blue recorder **Products are in compliance with

NDAA Section 889 Part B Guidelines

POEINJ

12.9.5W

Conformant with ONVIF Profile T

*with compatible Speco Blue recorder **Products are in compliance with

NDAA Section 889 Part B Guidelines

PoE Injector

5 year warranty

NDAA Compliant**





Ceiling Moun WMT1 Wall Mount

CMT1 Corner Mount









Power Supply

Pole Mount





O2VB1N

2.8mm fixed lens, white housing

2MP Bullet IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 100' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- · Line crossing, object detection, region intrusion, and video blurring detection*
- 3.5mm mic input
- IP67 compliant, weather resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant**

*with compatible Speco Blue recorder

* * Products are in compliance with NDAA Section 889 Part B Guidelines



.....

Pole Mount

Ceilina Moun

CLT1

IR H.265 (*) DAY MIGHT ANALYTICS SLOT POE IP67



OPERATES

IN -40°F

M

O2VB1VN

2.8-12mm varifocal lens, white housing

2MP Bullet IP Camera with Analytics and Junction Box

- Supports up to 2MP @ 30fps
- IR range: Up to 164' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Digital WDR (wide dynamic range)
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- Line crossing, object detection, region intrusion, and video blurring detection*
- 3.5mm audio input
- IP67 compliant, weather resistant
- Junction box included for convenience
- Built-in analytics with NR and HR Series Recorders

- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant*
- *with compatible Speco Blue recorder
- * * Products are in compliance with NDAA Section 889 Part B Guidelines



Optional Accessories



POEINJ

12.95W

PoE Injector









Optional Accessories

PMT1

OMPLIANT









2.8mm fixed lens, white housing

2MP Dome IP Camera

- Supports up to Full HD 1080p @ 30fps
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 98' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Glacier Series: Operates -40°F
- IP66 compliant, weather resistant
- Conformant with ONVIF Profile S
- Built-in Junction box
- 5 year warranty
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines





2MP Bullet IP Camera with Junction Box

- Supports up to Full HD 1080p @ 30fps
- IR range: Up to 98' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- Built-in IR LEDs
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- 5 year warranty
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines








Optional Accessories





12.95W PoE Injector

O2VLD8 2.8-12mm varifocal lens, white housing



• Supports up to Full HD 1080p @ 30fps

- IR range: Up to 131' (depending on scene reflection)
- Adaptive IR LEDs reduce IR saturation
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- 5 year warranty
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines



2.8-12mm varifocal lens, white housing

2MP Bullet IP Camera with Junction Box

- Supports up to Full HD 1080p @ 30fps
- IR range: Up to 131' (depending on scene reflection)
- Adaptive IR LEDs reduce IR saturation
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- Glacier Series: Operates -40°F
- Micro SD card slot up to 128GB (card not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- 5 year warranty
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines



speco technologie



PSW5 12VDC

Power Supply

POEINJ

12.95W PoE Injector











Indoor | 2MP IP Camera/Smart Management Terminal

O2TML

Temperature Reading & Face Recognition Terminal

2MP Temperature Reading Panel with Face and Mask Recognition

- 8-inch LCD screen
- Supports IR high-accuracy body temperature measurement
- Can recognize faces with masks
- Triggers voice alarm when abnormal temperature or mask-less face is detected
- Deep learning algorithm with high face recognition accuracy rate
- Supports remote live view and two-way talk
- 12VDC power supply included (PSW5)

This device is not FDA approved and is not intended for use in the diagnosis or treatment of any disease or other conditions, nor should it be solely or primarily relied upon to diagnose or exclude a diagnosis of COVID-19 or any other disease, or in the cure, mitigation, treatment, or prevention of any disease.

**N8NRT (optional add on)





IP 2 H.265 SD 2



Includes Wall Mount

TMLPMT

Pole Stand



N8NRT

Smart Management Terminal For O2TML

	Configurations			
ſ	N8NRT1TB	N8NRT3TB	N8NRT6TB	N8NRT10TB
	N8NRT2TB	N8NRT4TB	N8NRT8TB	

EZ Wizards

- Setup: for quick system setup
- Network: network setup and port forwarding
- Record: quickly setup recording types
- EZ Search 2.0: quickly search events from thumbnails
- EZ Copy: copy what you are playing onto a USB flash drive

EZ Mobile - easy mobile setup for viewing on desktop or mobile apps

- Manages up to (8) O2TML Temperature Reading Panel Cameras (sold seperately)
- H.265 compression Store up to 2x more than H.264!
- 4K HDMI out and VGA monitor output
- 1 SATA port for up to 10TB of storage max
- Real-time display of all traffic data, abnormal temperature, mask off, block list, strangers and other data
- Real-time face capture and temperature measurement
- Real-time personnel information display, including name, area, temperature, mask on/off, company, etc.



** works only with O2TML

- Statistics of abnormal temperature and non-mask detection in recent 24 hours or 7 days
- Attendance management
- Statistics of the people information, including staff, allow list, block list, VIP, stranger and staff counts
- Face greeting view and settings via Web client
- Free US-based DDNS and P2P services
- Remote viewing via web browser or your mobile device
- 5 year warranty*

*Excludes HDDs



H8D6M

2.8-12mm motorized lens, white housing

8MP (4K) HD-TVI IR Motorized Dome Camera with Junction Box

- 30 built-in IR LEDs
- Supports up to 8MP @ 15fps
- Signal distance up to 1600ft.
- Digital WDR (wide dynamic range)
- Motorized lens
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*
- * Products are in compliance with NDAA Section 889 Part B Guidelines

Power Supply



TVIUTPPT HD Video Transceiver with Pigtail (Balun)

TVIUTP HD Video Transceive

FMT2 Mount

PMT1

Pole Mount

Optional Accessories

(use with wall mount)

Moun O4D6WM Dome Wal Mount

CLT4 Ceiling

CMT1 Corner Mount (use with wall mount)

HD 4K IR ZOOM P66

H8B6M

2.8-12mm motorized lens, white housing

8MP (4K) HD-TVI IR Motorized Bullet Camera with Junction Box

- 35 built-in IR LEDs
- Supports up to 8MP @ 15fps
- Signal distance up to 1600ft.
- Digital WDR (wide dynamic range)
- Motorized lens
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



12VDC

Power Supply



HD Video Transo

with Pigtail (Balun)



HD Video

Transceive





CMT1 Corner Mount





Indoor/Outdoor 8 MP (4K)/5 MP HD-TVI Cameras

H8T7M 2.8-12mm motorized lens, white housing

8MP (4K) HD-TVI IR Motorized Turret **Camera with Junction Box**

- Supports up to 8MP@ 15fps
- IR Distance: Up to 164' (depending on scene reflection)
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP67 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



12VDC

Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

TVIUTP HD Video Transceiver

PMT1 Pole Mount

(use with wall mount)

Ceiling Moun WMT1 Dome Wal Mount

CLT3

CMT1 Corner Mount (use with wall mount)

H5B1M

2.7-13.5mm motorized lens, white housing

5MP HD-TVI IR Motorized Bullet Camera with Junction Box

- Supports up to 5MP TVI, 2MP AHD/CVI and CVBS by dip switch
- True WDR (wide dynamic range) operation
- Motorized lens
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty

30

NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines







Optional Accessories







PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceive with Piatail (Balun)

TVIUTP HD Video Transceiver



HD 4K IR ZOOM IP67

Indoor/Outdoor | 5MP HD-TVI Cameras



5MP HD-TVI IR Motorized Turret Camera with Junction Box

- Supports up to 5MP TVI, 2MP AHD/CVI and CVBS by dip switch
- True WDR (wide dynamic range) operation
- Motorized lens
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



5MP HD-TVI Vandal Dome Camera with Junction Box

- Supports up to 5MP @ 20fps
- Built-in high powered IR LEDs
- Digital WDR (wide dynamic range)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines







Optional Accessories







PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceive with Pigtail (Balun) TVIUTP HD Video Transceiver











TVIUTPPT TVIUTP HD Video Transceiver with Pigtail (Balun) Transceiver

Indoor/Outdoor | 5MP HD-TVI Camera

HTB5TG 2.8mm fixed lens, dark gray housing

5MP HD-TVI Bullet Camera with Junction Box

- Supports up to 5MP @ 20fps
- Built-in high powered IR LEDs
- Digital WDR (wide dynamic range)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories



with Pigtail (Balun)



Power Supply

HD 4 INT IR TRUE 6 IP66

Transceive



2.8-12mm motorized lens, dark gray housing

4MP Flexible Intensifier Technology[®] HD-TVI Motorized Dome Camera with Junction Box

- Flexible Intensifier Technology® fits any lighting application
- Supports 4MP @ 30fps
- Adaptive IR LED's
- Motorized Lens
- True WDR (wide dynamic range) operation
- Full OSD operation through onboard control and UTC (TVI)
- 12VDC & 24VAC dual voltage operation
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- Chameleon CoverTM: snaps on and can be painted to match any décor!

NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories



TVILITP

HD Video

Transceive









TVIUTPPT HD Video Transceiver with Pigtail (Balun)

PSW.5 Power Supply

INTWM Dome Wal Mount

INTCM Corner/Pole Mount

HFB4M

2.8-12mm motorized lens, dark gray housing

4MP Flexible Intensifier Technology[®] HD-TVI Motorized Bullet Camera with Junction Box

- Flexible Intensifier Technology® fits any lighting application
- Supports 4MP @ 30fps
- Adaptive IR LED's
- Motorized Lens
- True WDR (wide dynamic range) operation
- Full OSD operation through onboard control and UTC (TVI)
- 12VDC & 24VAC dual voltage operation
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines

VLT4DG

2.8mm fixed lens, dark gray housing

4MP HD-TVI Vandal Dome Camera with Junction Box

- Supports up to 4MP @ 15fps
- Built-in high powered IR LED's
- Digital WDR (wide dynamic range)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines







Optional Accessories





PSW/5





HD Video Transceiver with Piatail (Balun)

TVIUTP HD Video Transceiver

12VDC Power Supply

PSW4 24VAC Power Supply

Corner/Pole Mount









Optional Accessories

TVIUTP

HD Video

Transceive





TVIUTPPT HD Video Transceiver with Piatail (Balun)



VLT4BG

2.8mm fixed lens, dark gray housing

4MP HD-TVI Bullet Camera with Junction Box

- Supports up to 4MP @ 15fps
- Built-in high powered IR LED's
- Digital WDR (wide dynamic range)
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines









TVIUTP HD Video Transceive

12VD Power Supply

HT471TG/HT471TW

2.9mm fixed lens, dark gray/white housing

4MP HD-TVI Mini-Turret Color Cameras

- 1/3" Progressive Scan CMOS, 4MP
- Compact size only 2.36" in diameter!
- 12 IR LEDs
- Cast aluminum construction
- Signal distance up to 1600 feet
- Full OSD operation via UTC (TVI output only)
- Vandal resistant
- IP66 compliant, weather resistant
- 12VDC operation
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



Optional Accessories







2MP Ultra Intensifier[®] Dome HD-TVI Camera with Junction Box

- Next generation of Intensifier[®] technology provides an even more vivid color image in low light situations
- · Preset image modes offer convenient settings for different environments
- Supports up to full HD 1080p resolution @ 30fps
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- IP66 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience
- Chameleon Cover[™]: snaps on and can be painted to match any décor!
- 5 year warranty
- TAA Compliant



Tile Ceiling

Flush Moun

*Products are in compliance with NDAA Section 889 Part B Guidelines

> INTPM Pendant

Mount





HD 2 MP WDR IP66 IK10

Optional Accessories







A Contraction (Contraction) (C

TVILITPPT

INTWM Dome Wal Mount

24VAC Power Supply

12VDC Power Supply

HD Video Transceiver with Pigtail (Balun)

HD Video Transceiver

HiB68

3.6mm fixed lens, dark gray housing

2MP Ultra Intensifier[®] Bullet HD-TVI **Camera with Junction Box**

- Next generation of Intensifier® technology provides an even more vivid color image in low light situations
- Preset image modes offer convenient settings for different environments
- Supports up to full HD 1080p resolution @ 30fps
- Built-in temperature and humidity sensor control automatic heater operation
- True WDR (wide dynamic range) operation
- Glacier Series: Operates -40°F
- IP68 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant

NDAA Compliant*

INTCM

Corner/Pole

Mount

*Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories





TVIUTPPT TVIUTP HD Video Transceiver HD Video with Pigtail (Balun) Transceive

HT7246T/HT7250T

2.8-12mm/5-50mm varifocal lens, dark gray housing

2MP HD-TVI Intensifier[®] T Dome Cameras with Junction Box

- Full HD resolution over coax
- Supports up to Full HD 1080p @ 30fps
- True WDR (wide dynamic range) operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- With presets for different scenarios
- Signal distance up to 1600 ft. (depending on coax quality)
- Full OSD operation through on-board control and UTC (up the coax)
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- Chameleon CoverTM: snaps on and can be painted to match any décor!
- 3 axis lens mount
- 12VDC & 24VAC dual voltage operation

- Vandal/tamper resistant
- IP67 compliant, weather resistant
- Junction box included for convenience
- UL listed
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



INTWM Dome Wal Mount

PSW4

Optional Accessories

24VAC Power Supply

TVIUTPPT PSW5 HD Video Transceiver with Pigtail (Balun) 12VDC Power Supply

HD 2 INT TRUE 22

COMPLIANT

T

HD Video Transceiver

Included White Chameleon Cover™

HTINT70T/HTINT702T

2.8-12mm/5-50mm auto iris varifocal lens, dark gray housing

2MP HD-TVI Intensifier® T Bullet Cameras with Junction Box

- Full HD resolution over coax
- Supports up to Full HD 1080p @ 30fps
- True WDR (wide dynamic range) operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets for different scenarios
- Signal distance up to 1600 ft. (depending on coax quality)
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- Full OSD operation through on-board control and UTC (up the coax)
- 3 axis lens mount
- 12VDC/24VAC dual voltage operation
- IP67 compliant, weather resistant
- Junction box included for convenience

- Vandal/tamper resistant
- UL listed
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



Optional Accessories





TVILITP

HD Video

Transceive







PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

PSW4 24VAC Power Supply

INTCM Corner/Pole Adapter







HTINT60T/HTINT601T 🚻 🖧 🂵 TWE 📖 🎁

3 axis lens mount

5 year warranty

TAA Compliant

NDAA Compliant*

* Products are in compliance with

Optional Accessories

NDAA Section 889 Part B Guidelines

• Vandal/tamper resistant

IP67 compliant, weather resistant

12VDC/24VAC dual voltage operation

2.8-12mm varifocal lens/3.6mm fixed lens, dark gray housing

2MP HD-TVI Intensifier[®] T Turret Cameras

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets for different scenarios
- Built-in heater and anti-fog glass reduces condensation
- Full OSD operation through on-board control and UTC (up the coax)
- Signal distance up to 1600 ft. (depending on coax quality)
- Additional 960H analog output
- True WDR (wide dynamic range) operation

PSW5

12VDC

Power Supply







INTCM Corner/Pole Adapter Power Supply



Pendant Mount (use with CVCJBD & 60PLATE

Dome Wall Mount (use with CVCJBD & 60PLATE)

CVCIBD Dome Junction Box (use with 60PLATE)

60PLATE Adapter Plate

CVC6246T/CVC6246TW

2.8-12mm auto iris varifocal lens, black/white housing

2MP HD-TVI Intensifier® T Indoor Dome Cameras

- 1/3" Sony Exmor CMOS, 2MP
- Full HD resolution over coax (HD-TVI)
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Presets for different scenarios
- 12VDC/24VAC dual voltage operation
- Full OSD operation via UTC
- True WDR (wide dynamic range) operation
- 3 axis lens mount
- Signal distance up to 1600 ft*
- Additional 960H analog output
- 5 year warranty
- TAA Compliant

NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



Optional Accessories



with Pigtail (Balun)



HD Video

Transceive



PSW4

24VAC

Power Supply



DFM1 Tile Ceiling Flush Mount

CVCWMINDT Indoor Wall Moun



INTWM





Power Supply

VLD5 2.8mm fixed lens, white housing




space technole

2MP HD-TVI IR Dome Camera with Junction Box

- Full HD resolution over coax (HD-TVI)
- Supports up to 2MP @ 30fps
- IR Range: 65' (depending on scene reflection)
- Supports HD-TVI, CVI, AHD, and 960H Analog
- True WDR (wide dynamic range) operation
- 12VDC operation (power supply not included)
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience
- 5 year warranty
- **Optional Accessories** * Products are in compliance with NDAA Section 889 Part B Guidelines CLT2 Ceiling Mount O5VLWM PMT1 CMT1 TVIUTP FMT1 PSW5 TVIUTPPT Pole Mount Dome Wall Corner Mount HD Video Transceiver HD Video Flush 12VDC Mount (use with wall mount) (use with wall mount) Mount with Pigtail (Balun) Transceive Power Supply

VLB5



2MP HD-TVI IR Bullet Camera with Junction Box

- Full HD resolution over coax (HD-TVI)
- Supports up to 2MP @ 30fps
- IR Range: 65' (depending on scene reflection)
- Supports HD-TVI, CVI, AHD, and 960H Analog
- 12VDC operation (power supply not included)
- IP67 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories







CLT1 Ceiling Moun



PSW5 12VDC Power Supply

TVILITPPT HD Video Transceiver with Pigtail (Balun)





HD 2 IR HD 1967

VLDT4G/VLDT4W

3.6mm fixed lens, dark gray/white housing

2MP HD-TVI Eyeball Cameras with Junction Box

- 1/2.9" 2MP Sony CMOS
- Multi-format HD (TVI, CVI, AHD, CVBS)
- 18 built-in IR LEDs
- Full OSD operation through UTC (up the coax)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories





TVIUTP

PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun) TVIUTP HD Video Transceiver

2.8-12mm motorized lens, dark gray/white housing

2MP HD-TVI Motorized Eyeball Cameras with Junction Box

- 1/2.9" 2MP Sony CMOS
- Multi-format HD (TVI, CVI, AHD, CVBS)
- 18 built-in IR LEDs
- Motorized lens
- Full OSD operation through UTC (up the coax)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines









PSW5 TV 12VDC HD Vide Power Supply with Pi

TVIUTP HD Video Transceiver

VLD6M 2.8-12mm motorized lens, white housing

2MP HD-TVI IR Motorized Dome Camera with Junction Box

- Full HD resolution over coax (HD-TVI)
- Supports up to 2MP @ 30fps
- IR Range: 98' (depending on scene reflection)
- Supports HD-TVI, CVI, AHD, and 960H Analog
- True WDR (wide dynamic range) operation
- 12VDC operation (power supply not included)
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*
- *Products are in compliance with NDAA Section 889 Part B Guidelines



12VDC

Power Supply

HD Video Transceiver

with Pigtail (Balun)



Transceiver



PMT1 Pole Mount

Optional Accessories

(use with wall mount)

Ceiling Mount WMT1 Wall Mount

CLT3

HD 2 IR TRUE NUITH COMPANY IN TRUE NUITH COMPANY IN TRUE NUITH COMPANY IN THE INTERNET OF COMPANY INTERNET. INTERNET OF COMPANY INTERNET OF COMPANY INTERNET. INT

speco technologies

CMT1 Corner Mount (use with wall mount)

VLB6

2.8-12mm varifocal lens, white housing

2MP HD-TVI IR Bullet Camera with Junction Box

- Full HD resolution over coax (HD-TVI)
- Supports up to 2MP @ 30fps
- IR Range: 165' (depending on scene reflection)
- Supports HD-TVI, CVI, AHD, and 960H Analog
- 12VDC operation (power supply not included)
- IP67 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories





TVIUTP

HD Video

Transceive



Pole Moun





PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

COMPLIANT

HT5940T HD 2 IR TRUE 202 MAR 2.8-12mm auto iris varifocal lens, dark gray housing 2MP HD-TVI Intense IR Dome Camera technologies TVI with Junction Box & Adapter Plate Included White Chameleon Cover™ Full HD resolution over coax (HD-TVI) IP67 compliant, weather resistant Supports up to Full HD 1080p @ 30fps Junction box and adapter plate Intense IR function – no saturation, IR intensity included for convenience • 5 year warranty adapts to subject to provide vivid image • True Day/Night operation - mechanical IR cut filter TAA Compliant • Full OSD operation through onboard control and UTC (up the coax) NDAA Compliant* 12VDC & 24VAC dual voltage operation *Products are in compliance with • Chameleon CoverTM: snaps on and can NDAA Section 889 Part B Guidelines be painted to match any décor! 3-axis lens mount **Optional Accessories** Additional 960H analog output INTPM True WDR (wide dynamic range) Pendant Mount operation (use with CVCJBD Built-in heater and anti-fog glass PSW5 TVIUTPPT **TVILITP** INTWM PSW4 INTCM & 59PLATE reduces condensation 12VDC HD Video Transceive HD Video 24VAC Corner/Pole Adapter Dome Wall Mount with Pigtail (Balun) (use with INTWM only) (use with CVCJBD & 59PLATE) Power Supply Transceiver Power Supply Vandal/tamper resistant

HT7040T

2.8-12mm auto iris varifocal lens, dark gray housing

2MP HD-TVI Intense IR Bullet Camera with Junction Box

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- Intense IR function no saturation, IR intensity adapts to subject to provide vivid image
- True Day/Night operation mechanical IR cut filter
- Full OSD operation through onboard control and UTC (up the coax)
- 12VDC & 24VAC dual voltage operation
- 3-axis lens mount
- Signal distance up to 1600ft
- True WDR (wide dynamic range) operation
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation

- Vandal/tamper resistant
- IP67 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines













HD 2 IR TRUE



PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

TVIUTP HD Video Transceiver

PSW4 INTCM 24VAC Corner/Pole Power Supply

Adapter

INTJBS Sauare Junction Box

41

Optional Accessories

HT6041T 3.6mm fixed lens, dark gray housing

2MP HD-TVI Intense IR Turret Camera

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- Intense IR function no saturation, IR intensity adapts to subject to provide vivid image
- True Day/Night operation mechanical IR cut filter
- Full OSD operation through onboard control and UTC (up the coax)
- 12VDC & 24VAC dual voltage operation
- 3-axis lens mount
- Built-in heater and anti-fog glass reduces condensation
- True WDR (wide dynamic range) operation
- Signal distance up to 1600ft



- Vandal/tamper resistant
- IP67 compliant, weather resistant
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

PSW4

24VAC

Power Supply

*Products are in compliance with NDAA Section 889 Part B Guidelines



HD 2 IR TRUE





Optional Accessories

INTPM Pendant Mount INTWM Dome Wall Mount



60PLATE CVCIBD Adapter Plate Dome Camera Junction Box

HLED33DTB/HLED33DTW

TVIUTP

HD Video

Transceiver

TVILITPPT

HD Video Transceiver with Pigtail (Balun)

2.8-12mm auto iris varifocal lens, black/white housing

PSW5

12VDC

Power Supply

2MP HD-TVI IR Indoor Dome Cameras

- 1/3" Sony Exmor CMOS, 2MP
- Full HD resolution over coax @ 30fps (HD-TVI)
- Smart DNR reduces noises in low light
- Smart IR reduces saturation of objects within close proximity to IR LEDs
- 3-axis design, both wall and ceiling mountable
- Digital WDR (wide dynamic range)
- OSD for camera setting adjustments
- 12VDC/24VAC dual voltage operation
- Additional 960H analog output
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories







PSW5 12VDC Power Supply

TVIUTPPT TVIUTP HD Video Transceiver with Pigtail (Balun)

HD Video

PSW4 24VAC Power Supply





INTCM Corner/Pole Adapter

HTINT40T 3.6mm fixed lens, black housing

2MP HD-TVI Intensifier® T Indoor Mini-Board Camera

- Sony CMOS Sensor, 2MP
- Full HD 1080p @ 30fps (over coax)
- True WDR (wide dynamic range) operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- Full OSD operation through onboard control and UTC (TVI)
- Presets for different scenarios
- Additional 960H analog output
- 12VDC voltage operation
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



Accepts C & CS auto iris & manual type lenses, dark gray housing

2MP HD-TVI Intensifier® T Traditional Camera

- Full HD resolution over coax (HD-TVI)
- See color In almost complete darkness without IR LEDs
- Supports Full HD 1080p @ 30fps
- No problems caused by objects that reflect or absorb IR light sources
- True WDR (wide dynamic range) operation
- Presets for different scenarios
- Full OSD operation via UTC (TVI output only)
- Additional 960H analog output
- 12VDC/24VAC dual voltage operation
- Lens sold separately
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories



OSD CAMERA



PSW5 12VDC Power Supply

HD Video Transceiver H with Pigtail (Balun) Tra

TVIUTP HD Video Transceiver







Optional Accessories











PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

TVIUTP HD Video Transceiver Po

PSW4 VCH401HBMT 24VAC Housing with Heater, Power Supply Blower & Bracket

VFMP2.812DC5 2.8-12mm 5MP varifocal lens

VL62T 3.6mm fixed lens, black housing

2MP HD-TVI IR Bullet Camera

- Full HD resolution over coax (HD-TVI)
- Color Day/Night camera
- 12 IR LEDs with 60 ft. range (depending on scene reflection)
- 12VDC power supply included
- IP67 compliant, weather resistant
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with

NDAA Section 889 Part B Guidelines







Optional Accessories





PSW5

PSW5 12VDC HD Power Supply wit

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

rer 12VDC) Power Supply



3.7mm pinhole lens, operating PIR, white housing

2MP HD-TVI Camera in Operating PIR Housing

- Camera encased in working PIR
- Fully adjustable wall/ceiling mount included
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





Optional Accessories



PSW5 12VDC Power Supply TVIUTPPT HD Video Transceive with Pigtail (Balun) **PSW5** 12VDC Power Supply

CVC605CMT1

3.6mm fixed board lens, stainless steel housing

2MP Multi-Format Intensifier[®] T Corner Mount HD-TVI Camera

- Full HD resolution over coax (HD-TVI)
- Supports up to 1080p @ 30fps
- Perfect for elevators, hallways, etc.
- Full OSD operation via UTC (TVI)
- Multi-format HD (TVI, CVI, AHD, CVBS)
- Signal distance up to 1600 ft. (depending on coax quality)
- 12VDC operation (power supply not included)
- 5 year warranty
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines



3.6mm fixed lens, stainless steel housing

2MP HD-TVI Vandal Resistant Corner Mount Color Camera

- Full HD resolution over coax (HD-TVI)
- Supports up to 1080p @ 30fps
- Vandal resistant 90° corner mount camera
- Heavy duty housing is built to withstand blows from a 10 lb. sledgehammer
- 12VDC operation
- Additional analog output for 960H
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines

ADDITIONAL LENS SIZES: CVC607CMT2.2 CVC607CMT2.5





Optional Accessories







PSW5 12VDC H Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun) TVIUTP HD Video Transceiver





Optional Accessories



63

PSW5 12VDC HD Power Supply w

TVIUTPPT HD Video Transceiver with Pigtail (Balun) **TVIUTP** HD Video Transceiver

CVC675T

3.6mm lens, stainless steel housing

2MP HD-TVI In-Wall Camera

- Full HD up to 1080p @ 30fps
- Fits into a single gang electrical box (included)
- Brushed stainless steel faceplate
- 12VDC operation
- Additional analog output for 960H
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines







Optional Accessories





HLPR1G

5-50mm auto focus/zoom lens (10x auto focus/zoom), dark gray housing

2MP HD-TVI License Plate Capture Bullet Camera with Junction Box

- Full HD resolution over coax (HD-TVI)
- Full HD up to 1080p @ 30fps
- High-contrast imaging performance that delivers sharp, clear license-plate captures
- Supports full UTC control over coax for Zoom/Focus and camera's OSD
- Captures license plates up to 40mph
- IR Range: 131 ft. (depending on scene reflection)
- IP66 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty
- TAA Compliant
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines





HD 2 TVI MP IR ZOOM IP66









PSW5 12VDC Power Supply Pr





HTPTZ20T 4.7-94mm 20x optical zoom lens, white housing

2MP HD-TVI PTZ Dome Camera

- Full HD 1080p @ 30fps
- 20x optical zoom lens
- True WDR (wide dynamic range) operation
- True Day/Night function
- 240 preset positions
- 4 Alarm Inputs/2 Alarm Outputs
- 16x digital zoom
- Max 380°/sec speed
- Additional analog output for 960H

- Full OSD control via UTC (pan, tilt, and zoom)
- IP66 compliant, weather resistant
- 1 year warranty
- TAA Compliant
- NDAA Compliant'

*Products are in compliance with NDAA Section 889 Part B Guidelines



Optional Accessories





Transceiver

æ PSW4 24VAC Power Supply



WAC29DW

Wall/Ceiling Mount



PEN29DW Wall Mount Pendant Arm



APT32DW POI 28DW Adapter Plate for Pole Mount COR32DW or

POL28DW



COR32DW Corner Mount Adapter



HD 2 TRUE

Keyboard Controller

47

SecureGuard

VIDEO MANAGEMENT SOFTWARE



SecureGuard CMS (available for Windows & Mac)



Become a Surveillance Powerhouse.



We've simplified the surveillance management process by pre-loading our dynamic VMS on all SecureGuard® Servers, which means easy setup, reliability, and complete security.

- With SecureGuard® VMS, multiple users can view and playback video from the server and the sites from anywhere in the world
- Fully scalable to meet the growing demands of your business' surveillance needs
- Free software updates will keep you up-to-date with Speco's latest technological advancements
- and will keep your system performing optimally at NO ADDITIONAL COST

MODEL	SG319	SG519	SG719
Number of Cameras	up to 64 2MP cameras	up to 128 2MP cameras	up to 256 2MP cameras
Operating System	Windows 10 Enterprise	Windows 10 Enterprise	Windows 10 Enterprise
CPU	Intel® Xeon	Intel® Xeon	Intel [®] Xeon
Memory	16GB	16GB	16GB
Number of Storage Bays	8	24 (4U)	12
Maximum Raw Storage	Up to 128TB	Up to 384TB (4U)	Up to 192TB
RAID Levels	Yes (RAID 5, 6)	Yes (RAID 5, 6)	Yes (RAID 5, 6)
RAID Cache Protection	Yes	Yes	Yes
Hot Swappable	Yes (RAID 5, 6)	Yes (RAID 5, 6)	Yes (RAID 5, 6)
Network Ports	Dual Gigabit	Dual Gigabit	Dual Gigabit
Max. Throughput	360 Mbps	600 Mbps	1 Gbps
Redundant Power Supply	Yes	Yes	Yes
Warranty	3 year (NBD Onsite Repair)	3 year (NBD Onsite Repair)	3 year (NBD Onsite Repair

SecureGuard[®] Branding



Design

Custom | Have your company logo visible Branding | in our software at <u>NO COST!</u>

Speco will display your logo in the following areas: All desktop icons • Configurator tool splash screen • On the client-side toolbar • Across all background grids • Throughout the SecureGuard® Player • As a watermark on exported videos

For more information about SecureGuard® Branding Service, email sales@specotech.com or call 1.800.645.5516

We Design Your Surveillance System! SecureGuard

DON'T STRESS OVER WHAT SURVEILLANCE SYSTEM YOU NEED! SecureGuard® experi design a custom surveillance solution from the ground up with our SecureGuard® Servers at NO ADDITIONAL COST! Let our professionals select cameras and technologies that will I fit your needs or design a system that supports your existing surveillance system. Service



Be ANYWHERE at ANYTIME. SecureGuard[®] Apps

SecureGuard® Client • SecureGuard® Streamer (iOS only)



SecureGuard[®] Client App



SecureGuard® client app is a companion viewing app that allows you to connect and view sites from your SecureGuard[®] installation on the go. Download the app on your Android[™] and iPhone[®] devices **FREE**.

 Add multiple SecureGuard[®] Server or Speco recorder. IP camera installations using an IP address or DDNS

- Connect using your SecureGuard® login ID
- Create an unlimited number of custom layouts consisting of different sites and specific channels
- · View your sites along with the ability to listen to their audio
- Includes a help section with FAQ and contact information for our
- tech support team
- P2P capability (iOS only) • 2-way audio
- App Store



SecureGuard[®] Client for **Apple TV & Amazon Fire TV**

We created SecureGuard[®] client apps for Apple TV and Amazon Fire TV. These home entertainment devices allow you to view your security cameras then resume your favorite shows with ease. Use these devices also as a quick and easy spot monitors solution for smaller sites and forgo complicated wirings.

le and the Apple lo demarks of Apple Inc., regist App Store is a service mark of Apple Inc. Amazon's trademark is used under license from com, Inc. or its affiliates.



For full specifications and more information on SecureGuard® visit specotech.com



to their video in one of the four corners of the video frame. This creates an additional level of security, showing the video hasn't been tampered with

are vandalized, lose power or experience a disruption in communication between it and SecureGuard®. With health status monitoring, you won't miss another video loss from cameras down or individual channels of a

Recorders | 2MP HVRS

н	RN		H.265 EZ EZ EZ EZ BEZ OBJECT SAMARE P2F
HRN Se	eries - 2MP	H.265 Hybrid DVR with Smart Analytics	SERI
H6HR		nannel Hybrid Digital Video Recorder Channels plus 2 IP Channels	
	8 TVI	Channel Hybrid Digital Video Recorder Channels plus 4 IP Channels Channel Hybrid Digital Video Recorder Channels plus 8 IP Channels	• Remote viewing via web browser, your Apple TV,
H6HRN2TB	urations H12HRN12TB	EZ Wizards - For ease of use and setup Camera: quickly discover and install all Speco IP cameras Setup: for quick setup of general settings	Amazon Fire TV, or your mobile device Easy video exporting via USB 5 year limited warranty** NDAA Compliant***
16HRN4TB 16HRN6TB 16HRN8TB 16HRL6TB	H 12HRN 16TB H24HRN 2TB H24HRN 4TB H24HRN 6TB	Network: network setup and port forwarding Record: quickly setup recording resolutions and recording type EZ Search 2.0: quickly search for events from thumbnails EZ Copy: copy what you are playing onto a USB flash drive	* with Speco Smart Analytic IP Cameras * * Excludes HDDs * * * Products are in compliance with NDAA Section 889 Part B Guidelines
5HRN 10TB 5HRN 12TB 5HRN 16TB 12HRN 2TB	H24HRN8TB H24HRN12TB H24HRN16TB H24HRN20TB	 H.265 compression - Store up to 2x more than H.264! 1 SATA port for up to 16TB storage (H6HRN, H12HRN) 2 SATA ports for up to 32TB storage (H24HRN) 1 eSATA port for an additional 8TB of storage (H12HRN, H24HRN) HDMI out and VGA monitor output 	specoaccess
12HRN4TB 12HRN6TB 12HRN8TB	H24HRN24TB H24HRN32TB	 Provided and VOA information output 2-way audio communication Smart Search - Specify a region on the camera view and search on changes in that area* Object and line crossing detection and alerts* 	WALL MOUNT
	Martia	 Alarm 4/8/16 inputs, 1/2/4 outputs Free US-based DDNS and P2P services 	View A Camera Event Tag
	Model	HRN 12	Optional Accessories

	Model		HRN		
(Channels	6	12	24	
	Bandwidth	16Mbps		32Mbps	
	IP Video Input		ERS 1V		
Video	Output	HDMI × 1 : 1 VGA × 1 : 19 BNC × 1 :	Vented Rack Shelf		
	Input	RCA x 4		RCA x 8	5 Port Gigabit Network Switch (4 ports PoE / 1 port Uplink)
Audio	2-way Audio	Take up channel one audio input			
	Output	RCA × 1 (linear, 600Ω)			
	Resolution	1080P/1080P Lite/720P/WD1/D1			P8S9G 9 Port Gigabit Network Switch
Recording	Frame Rate	Anal 720P/WD1/[(8 ports PoE / 1 port Uplink)		
	Mode	Manual, timer, motion, smart event			
<u>Champion</u>	HDD	SATA×1, up to 16TB SATA×2, up to 16TB per HDD		DD P16S18G 18-port Gigabit Network Switch	
Storage	eSATA	0		1, Max 8TB	with 16-ports PoE
Network	Interface	RJ 45 100Mbps × 1 RJ 45 1000Mbps × 1			
Power	Power Consumption	≤ 10W (without HDD)		P32536GM	
Vie	Viewing Clients		SecureGuard® VMS, SecureGuard® CMS, SecureGuard® Client, AppleTV, Amazon Fire TV, iOS, Android Speco Blue		

Recorders | 4K NVRS

N4NRN 4 Channel NVR with 4 Built-in PoE Ports N8NRN 8 Channel NVR with 8 Built-in PoE Ports N16NRN 16 Channel NVR with 16 Built-in PoE Ports Configurations N4NRN12TB N4NRN12TB N4NRN4TB N16NRN4TB N4NRN4TB		RN ies - 4K H.2	265 NVR with Smart Analytics	EZ EZ SEARCH WIZARDS SEARCH 2.0 ANALYTICS P	2P OBJECT DETECTION CROSSING
Configurations EZ Wizards COMPLIANT N4NRN2TB N8NRN167B - Camera: quickly discover and install all Speco IP cameras - Object and line crossing detection and alerts* N4NRN4TB N16NRN4TB - Setup: for quick setup of general settings - Network: network setup and port forwarding N4NRN6TB N16NRN4TB - Record: quickly setup recording resolutions and recording type - Setup: for quick setup and port forwarding N4NRN12TB N16NRN4TB - Record: quickly search events from thumbnails - EZ Copy: copy what you are playing onto a USB flash drive EZ Mobile - easy mobile setup for viewing on desktop or - Real time recording up to 8MP resolution (4K) at 30fps - Real time recording up to 8MP resolution (4K) at 30fps - Store up to 2x more than H.264! - NDAA Compliant*** N8NRN12TB N16NRN32TB - 4K HDMI out and one VGA monitor output - WIMARN 1 SATA port for up to 16TB of storage max - With Speco Smart Analytic Cameras **Eccludes HDDs - WANRN: 1 SATA port for up to 16TB of storage max - With Speco Smart Analytic Cameras	N8NR	N 8 Char	nnel NVR with 8 Built-in PoE Ports		
N4NRN21B N8NRN161B N4NRN21B N16NRN2TB N4NRN6TB N16NRN4TB N4NRN6TB N16NRN4TB N4NRN6TB N16NRN4TB N4NRN8TB N16NRN6TB N4NRN16TB N16NRN6TB N4NRN16TB N16NRN6TB N4NRN16TB N16NRN6TB N4NRN16TB N16NRN6TB N4NRN16TB N16NRN6TB N4NRN16TB N16NRN8TB EZ Search 2.0: quickly setup recording resolutions and recording type EZ Copy: copy what you are playing onto a USB flash drive EZ Mobile - easy mobile setup for viewing on desktop or mobile apps N8NRN2TB N16NRN12TB N8NRN4TB N16NRN32TB N8NRN6TB N16NRN32TB N8NRN6TB N16NRN32TB N8NRN12TB - Real time recording up to 8MP resolution (4K) at 30fps N8NRN12TB - KK HDMI out and one VGA monitor output N8NRN12TB - KK HDMI out and one VGA monitor output N8NRN12TB - N4NRN: 1 SATA port for up to 16TB of storage max N8NRN: 1 SATA port for up to 16TB of storage max * Excludes HDDs ****Products ree in compliance with NDAA Sect			EZ Wizards	COMPL	
IN IOINKIN: 2 SAIA DOFTS FOR UD TO 321D OF STORAGE MAX	N4NRN4TB N4NRN6TB N4NRN8TB N4NRN12TB N4NRN16TB N8NRN2TB N8NRN4TB N8NRN6TB	N 16NRN2TB N 16NRN4TB N 16NRN6TB N 16NRN8TB N 16NRN 12TB N 16NRN 16TB N 16NRN 24TB	 Setup: for quick setup of general settings Network: network setup and port forwarding Record: quickly setup recording resolutions and recording type EZ Search 2.0: quickly search events from thumbnails EZ Copy: copy what you are playing onto a USB flash drive EZ Mobile - easy mobile setup for viewing on desktop or mobile apps Real time recording up to 8MP resolution (4K) at 30fps H.265 compression - Store up to 2x more than H.264! 4K HDMI out and one VGA monitor output N4NRN: 1 SATA port for up to 16TB of storage max 	 Human and vehicle detection Smart Search - Specify a reginand search on changes in that Free US-based DDNS and P2 Remote viewing via web brownor your mobile device Easy video exporting via USE 5 year warranty** NDAA Compliant*** *with Speco Smart Analytic Cameras *Excludes HDDs ***Products are in compliance with 	1* ion on the camera view it area* 2P services wser, Apple TV, Amazon Fire T 3
Model NRN INTEGRATED W		Model			INTEGRATED WITH

	Number of Channels		4	8	16	sp			
171	Input	IP Camera	H.264 /	H.264 / H.265 Auto Detection (Max. 8MP)					
Video		Main Monitor	HDMI	HDMI (Max. 4K) and VGA (Max. Full HD)					
	Output	VGA		VGA					
	Network Input		4 Ch. IPC audio input	8 Ch. IPC audio input	16 Ch. IPC audio input				
Audio		2-way Audio		RCA x1		•			
		Local Output		RCA x1		•			
	Sup	ported Resolutions	8MP,	/5MP/4MP/3MP/1080F	P/720P				
		Codec	н.	264 / H.265 (Auto Detect	tion)				
D II	Max Fro	ame Rate per Channel	Any Resolution @ 30fps						
Recording	Re	ecording Mode	Analytics / Continuous / Motion / Sensor / Schedule / Manual						
		Pre-recording	Max. 5 seconds						
		Post-recording	Max. 10 Minutes						
	HDD	Capacity of 1 HDD	16TB						
Channen		Internal SATA Ports			2				
Storage	USB	Front		1 USB 2.0		7			
	0.58	Rear		1 USB 2.0					
		Digital Zoom		Live and Playback, Free Siz	ze				
Features	S	mart Analytics	Crowd Density, People Co	unting, Object Detection, T	ampering, Tripwire, Intrusion				
	S.M.A.R.T		Temperature,	Power On Time, Bad Sect	ors and Health				
Network	Bandwidth		40Mbps	80Mbps	96Mbps				
	Pov	ver Consumption		≤ 15W (without HDD)					
	Viewing Clients			Blue App, Internet Explore uard® for Apple TV & Ama					



Auto Live Camera Pop-Up View A Camera Event Tag



Recorders | 4K NVRS



Any Resolution@ 30fps

Max. 5 seconds

Max. 10 Minutes

16TB

1

1

1

Live and Playback, Free Size

Profile S,T

DC48V

 $\leq 5W$ (without HDD)

SecureGuard® for Apple TV & Amazon Fire TV

40Mbps/40Mbps



Viewing Clients

HDD

USB

Max Frame Rate per Channel

Recording Mode

Pre-recording Post-recording

Digital Zoom

Smart Analytics

ONVIF Support

S.M.A.R.T

Throughput (Recording/Total)

Input Voltage

Power Consumption

Capacity of 1 HDD

Internal HDDs

Front

Rear

Recording


Storage

Features

Network

Power

Recorders | 4K Facial Recognition NVR



Recorders | 4K NVR

4K H.265 N64NI		innel NVR				
Config	urations		ease of use and setup discover and install all Speco IP cameras		POWERED BY	
N64NR2TB N64NR6TB N64NR8TB	N64NR24TB N64NR30TB N64NR64TB	 Setup: for quick s Network: network 	setup of general settings k setup and port forwarding	Saud Saud Sauit	КУНАЖК	
N64NR 12TB	N64NR72TB		etup recording resolutions and recording type uickly find an event using time-sliced thumbnail	 Smart Search - Specify and search on changes 	a region on the camera view	
N64NR16TB	N64NR96TB		ordings with quick preview	Free US-based DDNS		
N64NR20TB	N64NR128TB		opy what you are playing onto a USB flash drive		eb browser or your mobile de	
			mobile setup for viewing on desktop or	 Easy video exporting v 		
		mobile apps		Remote control include		
			ng up to 8MP resolution (4K) at 30fps	• 5 year limited warranty		
		• H.265 compress	ion - Store up to 2x more than H.264!			
		• 4K HDMI out an	d one VGA monitor output, additional	*with Speco Smart Analytic Can	neras	
		storage via 2 eS/	ATA ports	* * Excludes HDDs		
		 8 SATA ports for 	up to 128TB of storage max			
		 Object and line a 	crossing detection and alerts*			
	Model		NR			
		Number of Channels	64		INTEGRATED WITH SPECO OCCE	
	Input	IP Camera	H.264 / H.265 Auto Detection (M	ax. 8MP)		
Video		Main Monitor				
	Output	Sub Monitor	1 HDMI			
	Net	work Input	64 Ch. IPC audio input		\smile	
Audio		dio/Local Output	RCA x 1		Auto Live Camera Po	
		ng Resolutions	8MP/5MP/4MP/3MP/1080p/720p		 View A Camera Event Tag 	
-		Codec	H.264 / H.265 (Auto Detection)		J	
-		Rate per Channel	Any Resolution@ 30fps			
ecording		rding Mode	Analytics / Continuous / Motion / Sensor / Schedule / Manual			
-		-recording	Max. 5 seconds			
-		t-recording	Max. 10 Minutes			
	HDD each HDD		16TB-			
TIDD		Internal SATA ports	8			
		eSATA	eSATA x2, max 8TB			
otorage	Front		1 (USB 2.0)			
itorage			2 USB: 1 USB 2.0, 1 USB 3	.0	Optional Accessories	
itorage	USB -	Rear	2 000. 1 000 2.0, 1 000 0			
Storage		Rear gital Zoom	Live and Playback, Free Siz	ie in the second se		
-	Diç			ion, Tampering, Tripwire,	P16S18G 18-port Gigabit Network	
-	Diç Smc	gital Zoom	Live and Playback, Free Siz * Crowd Density, People Counting, Object Detect	ion, Tampering, Tripwire,		
-	Diç Smc	gital Zoom Irt Analytics	Live and Playback, Free Siz * Crowd Density, People Counting, Object Detect Intrusion, License Plate Recogr	ion, Tampering, Tripwire, ition	18-port Gigabit Network	
eatures	Dig Smc ON' S	gital Zoom rrt Analytics VIF Support	Live and Playback, Free Siz * Crowd Density, People Counting, Object Detect Intrusion, License Plate Recogr ONVIF 2.6	ion, Tampering, Tripwire, iition ors and Health	18-port Gigabit Network Switch with 16-ports PoE	
Storage Features	Diç Smc ON' S Netw	gital Zoom Irt Analytics VIF Support .M.A.R.T	Live and Playback, Free Siz * Crowd Density, People Counting, Object Detect Intrusion, License Plate Recogr ONVIF 2.6 Temperature, Power On Time, Bad Sector	ion, Tampering, Tripwire, iition ors and Health	18-port Gigabit Network Switch with 16-ports PoE	

Recorders | 4K NVRS



N8NU 8 Channel NVR with 8 Built-in PoE+ Ports N16NU 16 Channel NVR with 16 Built-in PoE+ Ports

Configu	urations	EZ Wizards
, i i i i i i i i i i i i i i i i i i i		Camera: quickly discovers and installs IP cameras
N8NU2TB	N16NU2TB	Setup: for quick system setup
N8NU4TB	N16NU4TB	Network: network setup and port forwarding
N8NU6TB	N16NU6TB	Record: quickly setup recording resolutions and recording type
N8NU8TB	N16NU8TB	EZ Search: quickly search events from thumbnails
	N16NU12TB	EZ Copy: auto copy what you are playing onto a USB flash drive
N8NU12TB	IN IOINU IZIB	• Find and install IP cameras on the local network without needing
N8NU16TB	N16NU16TB	
		to locate the cameras manually
N8NU24TB	N16NU24TB	• Supports up to 4K (3840x2160) resolution for live view, recording,
N8NU32TB	N16NU32TB	and playback
N8NU40TB	N16NU40TB	• Video out: 1 HDMI, 1 VGA, 1 Main, Spot
N8NU64TB	N16NU64TB	• Plug & Play feature for Speco IP cameras with isolated traffic on
		the PoE ports
		• Supports H.265 and H.264 streams

- Up to 64TB storage from 4 internal SATA ports
- eSATA port for additional storage
- External DAS supported, up to 40TB
- 2-way audio communication





- Programmable recording on motion detection, sensor, schedule, continuous and manual modes
- Networkable with free US-Based Speco DDNS service
- Digital Deterrent[®] for triggering audio message via an event
- PC & Mac[®] compatible

4K EZ EZ P

- Smart (Museum) Search Quickly search for a specific video event without the need for motion setup
- Switch between low and high quality stream during simultaneous continuous + motion + sensor recording modes for storage optimization
- Remote monitoring/recording/playback/configuration/ software upgrades and PTZ control via internet
- RAID 1/5/10 support, RAID maximum capacity 16TB
- 5 year warranty*
- UL Listed
- TAA Compliant
- *Excludes HDDs

	Model		N8NU	N16NU												
	Input Max IP Channels Camera		8	16	YOUR LOGO HERE											
Video			H.265/H.264 A	Nuto Detection (Max. 4K)												
Video	0.1.1	Main Monitor	HDMI (Max. 4K)	and VGA (Max. Full HD)												
	Output Sub Monitor			CVBS	۲											
		Input/Output	8/1	16/1												
Audio		Audio Codec		G.711												
		2-Way Audio	Local Audio - Network	Client, Local Audio - IP Camera												
Alarm		Input/Output		4/1	WALL MOUNT											
		Compression	H.265/H.2	64 (Auto Detection)	CONFIGURABLE											
		Max Bitrate per Channel	44	4K @ 8Mbps												
Recording	Max Frame Rate per Channel		Any res	Any resolution @ 30fps												
		Recording Mode	Continuous/Motion	Continuous/Motion/Sensor/Schedule/Manual												
		Pre Recording/Post Recording	Max. 20 Seco	Max. 20 Seconds/ Max. 60 Seconds												
		Capacity of 1 HDD		Up to 16TB												
														Internal HDDs		4
C1	HDD	RAID	RAID 1/5/10 support,	RAID 1/5/10 support, RAID Maximum Capacity 16TB												
Storage			eSATA		1											
		Extension	External DA	S (Max 40TB, RAID)												
	USB	Front/Rear		2/1												
		Network Interface	1Gbps + 8 PoE	1Gbps + 16 PoE	Optional Accessories											
Network	Dynamic DNS		Yes	Yes (Free DDNS)												
	Sub-stream for Network		Max. 640x36	Max. 640x360 @ 30fps / Channel												
Power		Power Supply	100	100~240V AC												
	Viewing Clients		and Speco Player Mobil	b-Viewer, SpecaTech Multi-Client Softward e Viewer, SecureGuard® Client, Apple TV & Amazon Fire TV												

External Alarm Box Module

Recorders | 5MP HVRS

HRL Serie		5 Hybrid DVR w	IP HD HYB ith Smart Analytics	RID 5 H.265 EZ EZ SEARCH SEARCH	2-WAY AUDIO DETECTION ETHART P2P
H16H	4 Configu RL 16 Cł 8 Confi	rable Hybrid Chan nannel Hybrid igurable Hybrid Ch	gital Video Recorder nels (TVI or IP) plus 2 IP Channels Digital Video Recorder nannels (TVI or IP) plus 8 IP Channels ease of use and setup	 Smart Search - Specify a reg view and search on changes 	
Config	urations				
H6HRL3TB	H16HRL2TB		scover and install all Speco IP cameras	 2-way audio communication Alarm 4/8/16 inputs, 1/2/ 	1 outputs
H6HRL4TB	H16HRL4TB		up of general settings setup and port forwarding	Free US-based DDNS and P2	
H6HRL6TB	H16HRL6TB		serup and port forwarding up recording resolutions and recording typ		
H6HRL8TB	H16HRL8TB		ickly search for events from thumbnails	your mobile device	
H6HRL10TB	H16HRL12TB		, what you are playing onto a USB flash d	rive • Easy video exporting via USE	3
H6HRL12TB	H16HRL16TB	• Up to 5MP on a	ll channels, 4K on 1 channel (H6HRL)/	 5 year limited warranty** 	
H6HRL16TB	H16HRL20TB	all channels (H1		*with Speco Smart Analytic IP Cameras	
TIOTIKLIOID			up to 16TB storage (H6HRL)	**Excludes HDDs	
_	H16HRL24TB		r up to 32TB storage (H16HRL) ion - Store up to 2x more than H.264!		INTEGRATED WITH SPECO OCCESS
			r an additional 8TB of storage crossing detection and alerts*		• Auto Live Camera Pop-Up
	Model		HR	L	View A Camera Event Tag
	Channel	s	6	16	YOUR LOGO HERE
		vork Access & .fer Bandwidth	16/40Mbps	32/96Mbps	HERE
Video	Netwo	rk Access Format	8MP/5MP/4MP/3MP/1080	P/960P/720P @ 25/30fps	۲
	Output		HDMlx1: 4Kx2K/1920x1080/1280x1024 VGAx1: 1920x1080/1280/x1024/1024x768 BNCx1: CVBS (used as the main or spot output)		
		Input	RCA x 4	RCA x 8	WALL MOUNT
Audio	2-	way Audio	Take up channel o	one audio input	CONFIGURABLE
	Lc	ocal Output	RCA		
		cord Stream	Dual stream		
	ŀ	Resolution	4K/5MP/4MP/10		Optional Accessories
Recording	F	rame Rate	4K@6fps/7fps, 5MP@12f 1080P/720P/WD1@25		
		Bit Rate	32~721	Mbps	ERS1V Vented Rack Shelf
		Mode	Manual, schedule, motic	on, sensor, intelligence	
Storage		HDD	SATA x 1, max 16TB per HDD	SATA x 16, max 16TB per HDD	
	eSATA		eSATA x 1,	max 8TB	P16S18G 18-port Gigabit Network Switch

Viewing Clients

Interface

Power Consumption

Network

Power

SecureGuard[®], Speco Blue App, SecureGuard[®] Client, SecureGuard[®] for Apple TV & Amazon Fire TV

RJ45 10M/100M/100Mbpsx1

≤ 15W (without HDD)

RJ45 10M/100M

≤ 5W (without HDD)

55

with 16-ports PoE

36-Port Managed Gigabit Switch with 32-ports PoE and 4xSFP Uplink

P32S36GM

Recorders | 4K HVRS



Recorders | 4MP DVRS



	Model		D4VX	D8VX	D16VX	
		Number of Channels	4	8	16	
Video	Input	Camera Types		960H, HD-TVI	1/2/3/4MP	
video	0.1.1	Main Monitor	VGA and H	IDMI (Max. 1920x1080)	VGA and HDMI (Max. 3840x2160)	
	Output	Sub Monitor		CVBS or SPOT	(Selectable)	
Audio	In	put & Output		4 line input &	l line output	
Audio	2	-Way Audio		Local Port ↔ Ne	etwork Client	
Alarm	S	Sensor Input	4	4 or 8 (with Sensor Box)	4 or 16 (with Sensor Box)	
Aldrin	A	larm Output				
	Frame Rat	e with 4MP Cameras		15fps/cł	nannel	
Live	Frame Rat	e with 3MP Cameras	18fps/channel			
	Frame Rat	e with 2MP Cameras	30fps/channel			
-	Compression		H.264			
Recording	Resolution	2688×1520 (4MP)	10fps/channel		12fps/channel	
lecoraling	& Frame	2304×1296 (3MP)		13fps/channel	15fps/channel	
	Rate	1920x1080 (2MP)		15fps/cł	nannel	
		Capacity of 1 HDD		16T	В	
	HDD	Internal HDDs	1			
Storage		e-SATA		n/c		
	USB	Front		1		
	Rear					
Network	Interface			10/100/100	00 Base-TX	
Retwork	Du	val Streaming		Yes		
	Viewing Clients			SecureGuard® Cli	eco Player and Internet Explorer, ent, SecureGuard® for Apple TV TV, SecureGuard® Multi Client	

YOUR LOGO

WALL MOUNT ONFIGURABLE

ZIPKITS | Economical 5MP Kits

ZIPK4N1/ZIPK8N2 IP 5 IR H.265 EL POE POE

5MP, 4 & 8 Channel - Economical Kits

ZIPK4N1 4 Channel NVR with Built-in PoE, 1TB Four 5MP Turret IP Cameras ZIPK8N2 8 Channel NVR with Built-in PoE, 2TB Six 5MP Turret IP Cameras

O5K1: Camera Specifications

- Supports up to 5MP resolution
- 2.8mm wide angle lens
- True Day/Night operation(IR cut filter)
- IR range up to 100ft (built-in IR LEDs)
- Supports H.265/H.264 compression
- IP66 compliant, weather resistant

N4JLN/N8JLN: NVR Specifications

EZ Wizards: Simple network and system setup


- Record: quickly setup recording resolutions and recording type
- EZ Copy: easily copy what you are playing onto a USB flash drive
- EZ App Setup: Just a a QR code with the app to view your cameras on your mobile device
- Up to 8MP resolution for live view, recording, and playback
- Plug & Play get video automatically via the PoE ports without any setup
- Supports streams up to H.265 for reduced bandwidth and reduced hard drive space requirements
- QR code based network setup for easy remote access
- Free US-based DDNS service



- 4K monitor output
- Gigabit Ethernet port
- 1TB storage/2TB Storage
- Built-in S.M.A.R.T Technology (Self-Monitoring, Analysis, and Reporting Technology)
- Expansion available for up to 8 cameras
- Analytics available with optional O8K1A camera

- Facial Recognition
- Human Detection
- Vehicle Detection
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines



• Supports up to 8MP (4K) resolution

What's in the Box: • NVR with 1TB/2TB hard drive • Four/Six 5MP cameras • Four/Six 60ft Ethernet cables

- One 3ft Ethernet cable
- Remote control
- 2 x AAA Batteries
- HDMI cable



	Models		ZIPK4N1		ZII	PK8N2	
	Input	Max. IP Channels		4		8	
	Monitor Output			1 HDMI, 1 VGA		Optional Accessories	
Video	Display Resolutions		VGA: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080 HDMI: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080, 2560 x 1440, 3840 x 2160/EDID		•		
	Compression		H.265, H.264			O8K1A* Add-on 8MP (4K) Analytic Camera	
Recording	Resolution		8MP			0	
Recording	Bandwidth		128Mbps				
	Reco	rding Mode	Continuous/Motion			O5KJBD	
	USB		1 x USB 2.0 (Front), 1 x USB 2.0 (Rear)		Camera Junction Box		
Nationali	PoE		4 ports	(802.3af PoE)	8 ports (802.3af PoE)	
Network	Ethernet		RJ - 45 (100/1000M) Port				
	Viewing Clients		Speco Gray	Viewer (Windows, N Apple TV and	1ac), Speco Gray a d Amazon Fire TV	pp (iOS, Android),	O5KWMT Wall Mount

ZIPKITS | Wireless 2MP Kit

ZIPK8WN2 2MP, 8 Channel - Wireless Kit

ZIPK8WN2 8 Channel Network Wireless Video Recorder, 2TB Six 2MP Wireless IP Cameras

O2WK1N: Camera Specifications

- Supports up to 2MP resolution
- 3.6mm wide angle lens
- True Day/Night operation (IR cut filter)
- PIR function with white LED deterrent
- Digital WDR
- 12VDC operation
- IR range up to 65' (built-in IR LEDs) (depending on scene reflection)
- Built-in mic
- IP66 compliant, weather resistant

N8JWN: NVR Specifications

- EZ Wizard for easy network and system setup
- EZ Search: search events from thumbnails
- EZ Record: set up recording resolutions
- and recording type
- **EZ Copy:** copy what you are playing onto a USB flash drive
- **EZ App Setup:** just scan a QR code with the app to view your cameras on your mobile device
- Up to 2MP resolution for live view, recording, and playback*
- 2TB storage included
- 1 front and rear USB ports for mouse and exporting files
- HDMI output

H.265

- Motion Detection with notification alerts
- LAN port to connect to your network
- NDAA Compliant*
- *Products are in compliance with NDAA Section 889 Part B Guidelines

What's in the Box:

- NVR with 2TB hard drive
- Six 2MP Wireless cameras
- SIx 45' DC power extension cables
- One 3ft Ethernet cable
- Remote control (battery included)
- HDMI cable



JWN

	Models		ZIPK8WN2
	Input Max. IP Channels		6 Wireless
Video	٧	GA/HDMI	1 VGA/ 1 HDMI (1024x768, 1280x1024, 1280x720, 1440x900, 1920x1080, 2560x1440, 3840x2160)/ EDID (monitor resolution auto detection)
And	Simul	taneous Output	VGA and HDMI
Audio		Audio Out	No No
	Compression		H.265
	Resolution		2MP (1080p)
Recording	Frame Rate		Max. 60fps@1080p Main Stream: 1~15fps@1080p per channel Sub Stream: 1~15fps@640*360 per channel
	Bandwidth		Up to 12Mbps
	Recording Mode		Manual, Schedule (Continuous/Event), Event (Pre/Post)
	l	ive Stream	Max. 2MP @ 15fps (Auto fps, Auto bitrate)
	USB		USB 2.0, 2 ports (for mouse and backup/upgrade)
Network		Ethernet	1 RJ45 10/100 Base-T
Viewing Clients		ents	Speco Gray Viewer, Speco Gray Mobile App, Internet Explorer, SecureGuard® Client, SecureGuard® for Apple TV & Amazon Fire TV





THE BENEFITS

OUT-OF-THE-BOX READY

EMBEDDED LINUX OS

BROWSER-MANAGED SOFTWARE NO SOFTWARE OR SERVER TO INSTALL - USE YOUR FAVORITE BROWSER ON PC OR MAC

VIDEO INTEGRATION GENERATE RECURRING MONTHLY REVENUE BY OFFERING VALUE-ADDED SERVICES

MOBILE APP AND REMOTE MANAGEMENT

MANAGE YOUR SYSTEM ON THE GO WITH THE MOBILE APP AND GET THE BENEFITS OF EDGE MANAGEMENT FROM ANYWHERE WITH REMOTE MANAGEMENT

FULLY SCALABLE

HARDWARE AND SOFTWARE ARE FULLY SCALABLE UP TO 128 DOORS

Speco Access is a browser and mobile app managed access control system that is fully scalable. It offers many value-added benefits including eliminating on site tech calls with the Remote Management Console. This allows for all the benefits of edge management from anywhere. It is also integrated with our **NR and HR series recorders**, which adds live video viewing, event video tagging, and two-factor authentication with face recognition-enabled cameras and recorders for an extra level of security. With the dedicated mobile app, users can lock & unlock doors, view events & live or tagged video, and manage users, all from their smartphone.



Speco Access | Controllers & Readers

ACS

A1

Single Door Controller

- Out of the box ready browser managed
- Embedded Linux operating system
- 1 Reader In
- 1 Reader Out
- 2 Relays (Lock/Aux)
- 3 Inputs (REX, DPS, Aux) Global
- Scalable to 128 doors when used with A2E4/A2E4P
- UL listed 294 Series 7
- 5 year warranty
- NDAA Compliant*
- * Products are in compliance with NDAA Section 889 Part B Guidelines



MPILANT

Optional Accessories

PSDC24

12VDC 2A

Wall Power Supply



A2E4

2 door controller, expandable up to 4 doors, basic power

Two Door Controller

- Embedded Linux operating system
- Expandable up to 4 doors
- (when used with A2M board)
- 2 Readers In
- 2 Readers Out
- 2 Relays (Lock/Aux)
- 3 Inputs (REX, DPS, Aux) Global
- Scalable to 128 doors
- UL listed 294 Series 7
- 5 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



AIN





ACS PG7 A2M





2 door controller, expandable up to 4 doors, power package

Two Door Controller

Embedded Linux operating system

A2E4P

- Expandable up to 4 doors (when used with A2M board)
- 2 Readers In
- 2 Readers Out
- 2 Relays (Lock/Aux)
- 3 Inputs (REX, DPS, Aux) Global
- Scalable to 128 doors
- UL listed 294 Series 7
- 12V/24V selectable lock power
- 5 year warranty
- NDAA Compliant*
- * Products are in compliance with NDAA Section 889 Part B Guidelines



(VL COMPLIANT

Optional Accessories



A2M Expansion Board





Expansion Board (use with A2E4/A2E4P)

- Expands A2E4/A2E4P up to 4 doors
- 2 Readers (In/Out)
- 2 Relays (Lock/Aux)
- 3 Inputs (REX, DPS, Aux) Global
- UL listed 294 Series 7
- 5 year warranty
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines





61









Speco Access | Readers



Mullion Proximity Reader

- Up to 5 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- IP67 compliant, weather resistant
- Tamper resistant
- UL listed
- Lifetime warranty
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines







Proximity Reader

- Up to 8 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- IP67 compliant, weather resistant
- Tamper resistant
- UL listed
- Lifetime warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



Mullion Proximity Reader & Keypad

- Up to 5 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- IP67 compliant, weather resistant
- Tamper resistant
- UL listed
- Lifetime warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



COMPLIANT



Proximity Reader & Keypad

- Up to 7 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- IP67 compliant, weather resistant
- Tamper resistant
- UL listed
- Lifetime warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines







NDAA

Speco Access | Readers/Credentials



Contactless Smartcard Reader

- Up to 15 feet of read range
- Contactless smartcard reader solution with mobile access support
- Digital Radio Frequency Identification (RFID) platform
- Supports both sector and card serial number (CSN) reads
- Offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE) enabled smartphones or contactless smartcard module
- IP67 compliant, weather resistant
- Tamper resistant
- UL Listed
- Lifetime warranty
- NDAA Compliant*





ACS

Shown in Switch Plate

* Products are in compliance with NDAA Section 889 Part B Guidelines



Proximity Disc Tag

- Up to 3.5in contactless read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 cards
- Lifetime warranty
- Use with AP300HA, AP500HA, AP620HA, AP640HA
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



Proximity Key Ring Tag

- Up to 3.5in contactless read range
- Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 tags
- Lifetime warranty
- Use with AP300HA, AP500HA, ΑΡ620ΗΑ, ΑΡ640ΗΑ
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines







Long Range Receiver

- Up to 200 feet of read range
- Ultra high frequency (UHF) technology
- Receiver range covers a 360-degree radius and does not need to be installed in line-of-sight to the Transmitters to function
- IP65 compliant, weather resistant
- UL Listed
- 1 year warranty
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



ACS

APSC1

Clamshell Proximity Card

- Up to 8in contactless read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 cards
- Lifetime warranty
- Use with AP300HA, AP500HA, AP620HA, AP640HA
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines

APSI4

Proximity Card

- Up to 7in contactless read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 cards
- Lifetime warranty
- Use with AP300HA, AP500HA, AP620HA, AP640HA
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines









COMPLIANT



ACS

Speco Access | Credentials

ACS

ACS

ACS

APSM2

Proximity Credential

- Up to 7in read range
- Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 cards
- 1 year warranty
- Use with AP300HA, AP500HA, AP620HA, AP640HA
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines



Clamshell Smartcard Credential

- Up to 2.25in read range
- High-Security Encryption Technology
- Frequency 13.56MHz
- Fraudulent Data Detection Solution
- Lifetime warranty
- Pack quantity: 25 cards
- Use with ACSR35L
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines

ACSM2P

Imagable Smartcard Credential

- Up to 2.25in read range
- Frequency 13.56MHz
- High-Security Encryption Technology
- 1 year warranty
- Pack quantity: 25 cards
- Use with ACSR35L
- NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines



COMPLIANT

ACMC2

Mobile Credential for **Bluetooth Reader**

- Up to 15ft read range
- Supports both presentation and longer-range options
- Bluetooth Low Energy: operates with mobile ready readers
- High Security Encryption Technology: protected behind the smartphone's security parameters
- Respect for Privacy: easy one-time registration without disclosure of private information
- Pack quantity: 25 codes
- Use with ACSR35L NDAA Compliant*
- * Products are in compliance with

NDAA Section 889 Part B Guidelines



Smartcard Key Fob

- Up to 1 in read range
- High-Security Encryption Technology
- Frequency 13.56MHz
- Fraudulent Data Detection Solution
- Pack quantity: 25 cards
- 1 year warranty
- Use with ACSR35L
- NDAA Compliant*

* Products are in compliance with NDAA Section 889 Part B Guidelines



Long Range Transmitters

- Up to 200ft button press read range; Up to 3.5in presentation read range
- Proven Digital Ultra High Frequency (UHF) technology
- IP65 compliant, weather resistant
- UL listed Standard 294
- Pack quantity: 5 transmitters
- 1 year warranty
- Use with AWRR44, AP300HA, AP500HA, AP620HA, AP640HA
- NDAA Compliant*

NDAA Section 889 Part B Guidelines





ACS














Speco Access | Kits

ACKIT1

4 Door Access Control System

(1) A2E4P
 (1) A2M
 (4) AP300HA
 (1) APSC1 (pack of 25)
 (1) AP4 (License)
 NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines





ACS

ACS

ACKIT2DR

2 Door Access Control System

(1) A2E4P
 (2) AP300HA
 (1) APSC1 (pack of 25)
 (1) AP4 (License)
 NDAA Compliant*

*Products are in compliance with NDAA Section 889 Part B Guidelines

ACKIT2VID

4 Door Access Control System & Video Integrated System

- (1) A2E4P
- (1) A2M
- (4) AP300HA
- (1) APSC1 (pack of 25)
- (1) AP4 (License)
- (1) N8NRL2TB
- (4) O4D6
- (1) NVR (License)





ACS



Speco Access | Video Integration

speco access

Speco Access is browser based and mobile app managed for viewing events, door control, and **threat level lock down!**

Dashboard > Dashboard Floor * Defou	It Floor	http://mc.spectech.com	2185/7c=nvr_searchéloc	No-336hanneNo-1	Dasht Dasht Der Vite and Dor Vite and Correct Vite and Vite and Vite and Vite and Vite and	antra dasar Maler anaga cara dhadar
LOG	АСК 0			Door 1 MS € 6 8 AO 1		
Time	Device Name	User Name	Event Code	Event Description		
07-25-2019 04:00:26	192.168.20.167	admin	15107	Web User Login		• Auto Live Camera Pop-Up
07-25-2019 03:58:36	Door 1		600	Door Locked		
07-25-2019 03:58:32	Door 1		601	Door Unlocked (nvr1::Channel 1)		View A Camera

SEAMLESS INTEGRATION WITH SPECO'S NR SERIES NETWORK VIDEO RECORDERS

with 2 Factor Authentication



The **first factor** is the use of Speco's Facial Recognition solution that will check a database of your saved faces to see if the visitor is who they say they are.

Use Speco Access as **the second factor** security measure to filter your workplace, only letting in visitors with approved credentials. Our extensive line of readers, controllers, and credentials are perfect any application.

* Must use NRE recorder and face recognition - enabled cameras for this feature, fully configurable

WHY SPECO? HERE'S A FEW REASONS TO CHOOSE SPECO OVER THE COMPETITION!













- 5 Year Warranty We are confident in our quality!
- Included Junction Boxes One less thing for the technicians to worry about during the installation! Comes included in the box at no additional cost!
- The S.E.A.L Team Dedicated team to build the quote for you, FAST!
- Family Owned Easy to work with & nimble.
- Award Winning Marketing Support We can help you generate demand to increase your business.
- Great, Fast, Tech Support Get your techs in and out quicker.
- Speco University We help educate your employees with CEU accredited courses.
- Advanced Analytics Cameras and recorders with analytic capabilities, such as: Facial Recognition, License Plate Recognition, Vehicle Detection, Human Detection, Line Crossing, Object Detection, and Smart Search. A great high margin RMR opportunity.
- Video, Audio, & Access Control Integration Seamless integration between the latest technologies.
- Immix Integrated Another way to add RMR to every installation for video verification.
- NDAA Compliant Products Meet the standards for installation in U.S. Government facilities. *See our website specotech.com for a list of available models.
- Patented Technologies Exclusive to Speco
 - Digital Deterrent
 - Wall Mount Recorders
- EZ WIZARDS SIMPLIFY YOUR INSTALLATIONS CAMERA - Discovers and Installs All Speco IP Cameras Automatically SETUP - Breeze through Setup of General Settings with ease RECORD - Set Recording Resolution and Recording Type SEARCH - Search through 24 Hours of Video Events From Thumbnails in Seconds
 - COPY Copy What You Are Playing Onto a USB Flash Drive



• Product Availability - Speco is fully stocked and can fill your order today.

Speco technologies Giving You More. 800.645.5516 | specotech.com

speco technologies[®] Giving You More.

Contact us at: **sales@specotech.com** Toll Free: 1.800.645.5516 • Metro NY: 631.957.8700 200 New Highway, Amityville NY 11701 www.specotech.com



EDITION: V.4 Rev. 10.11.2021

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.