

DTK-MRJ45 Series

RJ45 Series Modular Surge Protection



Product Features

- Protects all four pairs, RJ45 connections
- Multi-stage, hybrid design provides the best possible protection
- Current-limiting circuitry minimizes risk to connected equipment
- Five voltage levels available to protect all types of voice/data applications
- Automatic resetting fuse and sneak current protection.

Applications

- Central Office Lines
- Building-to-Building Runs
- Station Lines
- Low Voltage Data
- P.O.T.S. Lines

Accessories

- DIN Rail Mounting Kit – Part Number DTK-DRK

DITEK's DTK-MRJ45 Series protects vital data and communication circuits from surge-induced damage. Convenient RJ connections protect four voice, data and/or signal pairs. MRJ45 Series surge protectors are easily installed at a building's incoming entry, and at the equipment being protected.

Technical Specifications

DTK-MRJ45SCP	X	LV	OPX	RUV
Service Voltage:	12V	24V	48V	130V
MCOV:	18VDC	33VDC	66VDC	175VDC
Clamping Voltage:	47V	47V	82V	204V
Protection Modes:	Tip-Ground, Ring-Ground (All)			
Surge Current Rating:	2,000A/pair (5V – 48V) 9,000A/pair (130V)			
Max Continuous Current:	0.15 Amps			

Mechanical Characteristics

Connection Method:	RJ45
Housing:	ABS
Operating Temperature:	-40°F - 158°F (-40°C - 70°C)
Maximum Humidity:	95% non-condensing
Dimensions:	3.0"L x 1.7"W x 1.2"H (76mm x 43mm x 30mm)
Weight:	4 oz (113 g)

Quality, Standards & Approval

Agency Approvals:	UL497A
Warranty:	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

