

IP Visual Display Speakers for Visual Alerting and Audible Notification.

With a 15.6" LCD display, high-intelligibility speakers, and high visibility LED flashers, the 8410 can produce highly attention-grabbing visual and audible messages for emergency and non-emergency events.



Algo's 8410 IP Visual Display Speaker is a SIP-compliant notification device that is comprised of three core components - a 15.6" LCD screen, high-intelligibility speakers, and high visibility LED flashers - to deliver highly effective visual and audible communication. The 8410 allows for customizable and flexible paging, notification, and alerting capabilities.

The primary element of the 8410 is the LCD display. With unlimited visual possibilities, the screen can produce scrolling text, flashing announcements, full-color images, or key data points such as dates and times. Combined with LED backlighting and wide-angle viewing, the visual display can be seen from anywhere in a room or along a hallway. It can be customized to complement an audio announcement or to bring communication to an audio-less environment.

For audible alerting, the 8410 offers similar functionality and voice quality as any Algo speaker, delivering wideband HD audio for clear voice communication and attention grabbing audible alerting. An embedded microphone is included to enable ambient noise response and talkback capabilities.

The LED flashers provide additional awareness for important messages. When no announcement or notification is needed, a variety of messages can be displayed, including images, text, or an NTP clock.

FEATURES

- 15.6" wide-angle viewable LCD display for off-axis visibility.
- Unlimited and customizable visual display capabilities with over 16 million colors.
- Display for digital or analog NTP clock, scrolling text, and emergency notifications.
- PoE+ (802.3at) and PoE++ (802.3bt) Powered.
- Remotely manageable for easy monitoring, maintenance, and management.
- Wideband audio (G.722 voice codec) for speech intelligibility and high quality audio.
- Sleep mode and screen dimming to save on power usage.

AVAILABLE DOUBLE-SIDED AS 8420

- Dual direction 15.6" LCD displays, wideband speaker, and LED flashers to deploy in hallways or open corridors.
- Contains the same core features and applications as 8410.
- Ceiling and wall-mount orientation available via included bracket.

POWER	
POE POWERED	Recommended: PoE++ (IEEE 802.3bt Type 3 Max 51W) Optional: PoE+ (IEEE 802.3at Type 2 Max 25.5W)
SIP	
EXTENSIONS	50 Page & 10 Alerting/Ring extensions with multicast scalability
TRANSPORT PROTOCOLS	UDP, RTP, TCP
SECURITY	TLS, MTL, SRTP
MULTICAST COMPATIBILITY	
MULTICAST	RTP Multicast (Send & Receive 50 zones)
THIRD PARTY MULTICAST	Polycom™ Group Page, Singlewire™ InformaCast, Syn-Apps™ Revolution
DIGITAL IO	
RELAY CONFIGURED AS INPUT	Normally open or normally closed dry contact supervision. Compatible with Algo 1202, 1203, and 1204 Accessories.
API	
API	RESTful
AUDIO	
AUDIO CODECS	G.711 A-law, G.711 u-law, G.722, Opus 48 kHz.
SPEAKERS	3 x Neodymium magnet with polypropylene cone
FREQUENCY RESPONSE	150 – 19,000 Hz (- 10 dB)
DRIVER SENSITIVITY	92 dB 1m/1W (1 kHz sine wave)
MAXIMUM SPL	Peak 106 dBA/1m
MAX AUDIO POWER	8 Watts
AUDIO MEMORY + FORMAT	1 GB user space for WAV or MP3 files
MICROPHONE	Omni-directional, talkback and ambient noise monitoring
AUDIO CONTROLS	Volume, AGC, Latency, LF Cut
ANTI-FEEDBACK DELAY	Cache to memory and release
VIDEO	
LCD VIEWING AREA	13.5" x 7.6" (34.4 cm x 19.4 cm)
RESOLUTION	1920 x 1080 @ 60 fps
VIEWING ANGLE	88 deg (horizontal and vertical)
COLOR	16.7 M
BACKLIGHT	LED Auto-dimmable
CONTRAST	1000:1
NETWORK	
NETWORK	IPv4, IPv6, DHCP, VLAN, MDNS
LINK LAYER	LLDP, CDP
QOS	DSCP (SIP, RTP, RTCP)
WEB INTERFACE	HTTP, HTTPS
PROVISIONING	TFTP, FTP, HTTP, HTTPS, DHCP Options 66, 150, 160 Reboot via SIP Check-sync
NAT	STUN, TURN, CRLF Keep Alive, SIP Outbound
ADDRESS RESOLUTION	DNS, SRV Record
SUPERVISION	SNMP V1.3, RTCP, Algo 8300
REDUNDANCY	Secondary & Tertiary SIP Servers
ENVIRONMENTAL + MECHANICAL	
ENVIRONMENTAL	32 to 104 deg F (0 to + 40 degC); 10-95% RH non-condensing. Dry indoor locations only.
MECHANICAL	15.25" x 11.5" x 2.0"
COMPLIANCE	
IEC 62368-1, IEEE 802.3-2018, RoHS, CE, FCC Class A, CISPR 32 Class A, CISPR 24, CSA/UL (USA & Canada),	
FIRMWARE	

These specifications refer to the Algo 8410 running firmware 5.2 and above.

FRONT



BACK



ORDERING CODES:

- 8410** IP Display Speaker
- 8420** IP Dual-Sided IP Display Speaker

COMPATIBLE ACCESSORIES:

- 1202** Customer/Emergency Assistance Button
- 1203** Wall Switch Single Gang Blue LED
- 1204** Volume Control



1202



1203



1204

DC8410 2023 © Algo Communication Products Ltd. All rights reserved. Algo® is a registered trademark of Algo Communication Products Ltd. TM Poly, Polycom, Singlewire, InformaCast, Syn-Apps, Revolution are trademarks of their respective owners. Note: Specifications are subject to change without notice. Some features may only be available in specific firmware or hardware releases.