



# GXP2160

## Our most powerful Enterprise IP Phones

Our most powerful Enterprise IP Phone, the GXP2160 is a Linux-based device with 6 lines, 5 XML programmable soft keys, and 5-way conferencing. HD audio and a 4.3 inch color LCD screen create high quality calls, while the 24 BLF keys, Bluetooth, USB and EHS add versatility. The GXP2160 is perfect for Enterprise & SMB customers with the need for quality and versatility in their desktop communications.



**6 LINES**

6 lines, with up to 6 SIP accounts, 6 dual-colored line keys



**Gigabit**

Dual-switched auto-sensing 10/100/1000mbps network ports



24 dual-colored and programmable BLF/speed dial keys



Built-in Bluetooth for syncing headsets and mobile devices for contact books, calendars & call transferring



**HD**

HD audio to maximize audio quality and clarity, full-duplex speakerphone



**PoE**

Built-in PoE to power the device and give it a network connection



**EHS**

Supports EHS compatible Plantronics headsets



Automated provisioning options include TR-069 and XML config files



Built-in USB ports for importing/exporting data



TLS and SRTP security encryption technology to protect calls and accounts



**5 WAY**

5-way audio conferencing for easy conference calls

<b>Protocols/Standards</b>	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPv6
<b>Network Interfaces</b>	Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE
<b>Graphic Display</b>	4.3 inch (480x272) TFT color LCD
<b>Bluetooth</b>	Yes, Bluetooth V2.1
<b>Feature Keys</b>	6 line keys with up to 6 SIP accounts, 24 speed-dial/BLF extension keys with dual-color LED, 5 programmable context sensitive softkeys, 5 navigation/menu keys, 11 dedicated function keys for : MESSAGE (with LED indicator), PHONEBOOK, TRANSFER, CONFERENCE, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-
<b>Voice Codexs</b>	Support for G.729A/B, G.711 $\mu$ /a-law, G.726, G.722(wide-band), and iLBC, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC
<b>Auxiliary Ports</b>	RJ9 headset jack (allowing EHS with Plantronics headsets), USB
<b>Telephony Features</b>	Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance (SCA)/bridged-line-appearance (BLA), downloadable phonebook (XML, LDAP, up to 2000 items), call waiting, call log (up to 500 records), customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones and music on hold, server redundancy and fail-over
<b>Sample Applications</b>	Weather, currency, news, XML
<b>HD Audio</b>	Yes, both on handset and speakerphone
<b>Base Stand/Wall Mountable</b>	Yes, allow 2 angle positions
<b>QoS</b>	Layer 2 (808.1Q, 802.1p) and Layer 3 (ToS, DiffServ, MPLS) QoS
<b>Security</b>	User and administrator level passwords, MD5 and MD5-session based authentication, AES based secure configuration file, SRTP, TLS, 802.1x media access control
<b>Multi-language</b>	English, Arabic, Chinese, Croatian, Czech, Dutch, German, French, Hebrew, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Slovenia, Spanish, Turkish
<b>Upgrade/Provisioning</b>	Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using TR-069 or encrypted XML configuration file
<b>Power &amp; Green Energy Efficiency</b>	Universal power adapter included: Input: 100-240VAC; Output: +12V, 1.0A Integrated PoE (Power-over-Ethernet) 802.3af, Max power consumption: 6W
<b>Physical</b>	Dimension: 275.5mm (W) x 206mm (L) x 46.5mm (H); Unit weight: 0.98kg; Package weight: 1.62kg
<b>Temperature and Humidity</b>	0 ~ 40°C (32 ~ 104°F), 10 ~ 90% (non-condensing)
<b>Package Content</b>	GXP2160 phone, handset with cord, base stand, universal power supply, network cable, Quick Start Guide